



FCS-5095 Version: 1

! Power supply unit is to be ordered separately.

Fixed IP Network Camera, 8-Megapixel, H.265/264, 802.3at PoE, 4.3X Optical Zoom, IR LEDs, Indoor/Outdoor, Vandalproof

The LevelOne FCS-5095 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 8-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5095 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 8-Megapixel high-definition resolution
- Video compression: H.264/H.265
- Supports 4.3X optical zoom
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK10-rated housing
- Weatherproof IP67-rated housing
- Built-in infrared LEDs for night viewing up to 50m
- Built-in Micro SDHC/SDXC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, IEEE802.1x

Image Sensor:

1/2.5" Progressive Scan CMOS

Lens:

Motorization 2.8 - 12 mm @ F1.4

Port:

1 x RJ-45 10/100 Mbps PoE port

Power Connector

1 x MicroSDHC/ MicroSDXC card slot

1 X 1Vp 1Vp-p composite output (75 Ω/BNC)

1 X Terminal Block DI/DO (max 12 VDC, 30 mA)

1 x Audio in/Out

1 X Terminal Block 12 VDC

**Button/Knob:**

Reset Button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

IR LEDs for illumination up to 50m

Shutter Time:

1/3 ~ 1/100,000 sec

Angle of View:

Horizontal field of view: 120° to 36°

Vertical field of view: 62° to 20.5°

Diagonal field of view: 149° to 42°

Pan/Tilt/Zoom:

4.3X Optical Zoom

Video Compression:

H.265, H.264, H264+

Resolution:

50Hz: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

Video Format:

AVI

Power Input:

12 V DC ± DC ± 25%, PoE (802.at)

Power Consumption:

12 VDC, 1.5A, max 17W

PoE (802.3at, 42.5V to 57V), 0.1A to 0.5A, max. 19W

Data Transfer Rate:

32 Kbps to 16 Mbps

Features

General:

rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser.

PoE:

PoE(802.3at)

Security:

One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter

Management:

Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error, Alarm input, Alarm output, Line crossing detection, intrusion detection

Video:

120dB Wide Dynamic Range

Support 1 fixed region for mainstream and sub stream separately

Performance

Number of Clients:

32

Storage Capacity:

Built-in microSD/SDHC/SDXC slot, up to 128 GB

Frame Rate (fps):

20 fps (3840 × 2160)

Minimum illumination:

Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR

Color: 0.014 Lux @ (F1.4, AGC ON), 0 Lux with IR

Environment

Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

Humidity (Non-condensing):

95% or less

Physical Specifications

Dimensions (W x D x H mm):

144.13x332.73 mm (5.67"x 13.10")

Weight (g):

1893 g (4.17l b.)

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Safety:

IK10

Environmental Test:

IP67

Others:

ONVIF

Others

Viewing Systems:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Order Information

FCS-5095

Package Contents

FCS-5095

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.