



FCS-1158 Version: 1

HUBBLE Varifocal IP Network Camera, 5-Megapixel, H.265, 802.3af PoE

The LevelOne FCS-1158 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for indoor IP surveillance networks. Offering clear, sharp imagery with 5-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-1158 should be an essential part of any security deployment that requires smart, reliable indoor cameras.

Key Features

- 5-Megapixel high-definition resolution
- Video compression: H.264, H.265, MJPEG
- Auto Back Focus (ABF) function makes camera focusing easier
- P-iris automatic lighting control for high image quality
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- BNC connector for analog video output
- Supports 2 video streams simultaneously
- Digital input/output (1DI/1DO) for sensor and alarm
- Built-in Micro SD/SDHC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Image Sensor:

1/1.8" Progressive Scan CMOS

Lens:

Vari-focal Lens with f3.6-10mm/F1.5-F2.8, P-Iris

Port:

- 1 x RJ-45 10/100/1000 Mbps PoE port
- Power Connector
- 1 x MicroSDHC/ MicroSDXC card slot
- 1 X 1Vp 1Vp-p composite output (75 Ω/BNC)
- 1 X Terminal Block DI/DO
- 1 X RS-485/RS-422, Terminal block
- 1 x Audio in/Out
- 1 X Built-in Microphone
- 1 X Terminal Block 12 VDC

**Button/Knob:**

Reset button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

Shutter Time:

1/5 ~ 1/16,000 sec (manual mode); 1/5 ~ 1/16,000 sec (auto mode)

Angle of View:

89.1° - 38.2°

Video Compression:

H.265, H.264 , MJPEG

Resolution:

30 fps at 2592 x 1944

30 fps at 2048 x 1536

30 fps at 1920 x 1080

30 fps at 1280 x 960

30 fps at 1280 x 720

30 fps at 800 x 600

30 fps at 640 x 480

30 fps at 320 x 240

Output Video Format:

RAW

Audio Compression:

G.711

Power Input:

DC 12V/0.6A Terminal block

PoE (802.3at)

Power Consumption:

DC 12V / 7W; PoE Class 3 (IEEE802.3af) / 12.95W

Data Rate:

128 Kbps -20 Mbps (per stream)

Storage Capacity:

MicroSDHC / MicroSDXC memory card slot (card not included), up to 64GB

Features

General:

Video motion detection (3 regions); External device through digital input; Sound detection; Tampering detection

PoE:

PoE Class 3 (IEEE802.3af) / 12.95W

Security:

One-key Reset, Heartbeat, Password Protection, Change camera settings; Command other devices; E-mail notification with snapshots;

Save video or snapshot to local storage; Upload video or snapshot to FTP server; Activate external device through digital output

Video:

P-Iris;

Extreme WDR (100 dB);

White balance: automatic;

Brightness; Defogging; Contrast; Sharpness (auto);

Auto gain control; 2D+3D digital noise reduction;

Flickerless; Digital Image Stabilizer;

www.level1.com
30 fps at 2592 x 1944;

Wide Angle

Audio:
8kHz, Mono; G.711

Performance

Number of Clients:
16

Frame Rate (fps):
30 fps at 2592 x 1944
30 fps at 2048 x 1536
30 fps at 1920 x 1080
30 fps at 1280 x 960
30 fps at 1280 x 720
30 fps at 800 x 600
30 fps at 640 x 480
30 fps at 320 x 240

Minimum illumination:
Color: 0.1 lux at F1.5;
B/W 0.05 lux at F1.5 (AGC on)

Environment

Operating Temperature (°C):
10°C ~ 50°C (14°F ~ 122°F)

Operating Humidity (Non-condensing):
10% ~ 90% RH

Physical Specifications

Dimensions (W x D x H mm):
125 x 58 x 62 mm (4.92" x 2.28" x 2.44")

Weight (g):
360 g (0.7956 lb)

Color:
White

Approval and Compliance

EMI/EMS:
CF/FCC

Others:
ONVIF

Others

Supported Browsers:
Windows 7,8,10

Compatibility:
IE 9 above

Order Information

FCS-1158



Package Contents

FCS-1158

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.