


### Open Frame Touch Monitor

#### HO 161 HTB

15.6" / 39,6cm Diagonal  
LED Backlight – Format 16:9

- 1920 x 1080 Resolution Full HD 1080P
- 10-Point Touch P-Cap Technology
- 170° / 170° Ultra Wide Viewing Angle
- Dual Input: HDMI + VGA
- IP54 (front) Rating Level
- 12 Volt External Power Supply
- ≥7H Toughened Hard Panel Surface
- TP Module Thickness 3.3mm
- Touch-Through Glass (available upon request\*)
- Sturdy Metal Case
- VESA Mount and Multiple Mounting Options
- Orientation: Landscape, Portrait, Face-Up



15.6" / 39,6 cm

Part. No.: HO 161 HTB

#### SIZE, RESOLUTION



15.6"  
16:9 Aspect Ratio



Full HD  
1920 x 1080

#### CONNECTIVITY, IP LEVEL




VGA  
HDMI



IP 54  
Water & Dust  
Protection

#### VIEWING ANGLE, VESA



170° Wide  
Viewing Angle



VESA  
Wall-Mountable

#### OTHER FEATURES




10 Points  
Touch



Touch to  
USB Link

## HO 161 HTB 15.6" Open Frame Touch Monitor

Display Size	39.6 cm / 15.6" Diagonal
Panel Type	TFT – LED Backlight
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	250 cd/m <sup>2</sup> (Panel) – 212 cd/m <sup>2</sup> (Monitor)
Contrast (Typ.)	800:1 (Typical)
Display Area	344,16 x 193,59 mm
Viewing Angle L/R; U/D	170° H / 170° V (CR > 10)
Response Time	30 msec
Pixel Pitch	0.17925 (H) X 0.17925 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch Material Glass + Glass
Display Colors	256K Colors
Horizontal Frequency	30 ~ 80 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	VGA
Input 2	HDMI
Input 3	USB Interface (Touch)
Speakers	-
Power Consumption	On: 7W; Stand-by: 0,121W; Off: 0,109W
Power Range	External Power Supply Input: AC 100 ~ 240 Volt; 50 ~ 60 Hz Output: DC 12V – 3A
Product Dimensions	405 x 36,4 x 256 mm (W x D x H)
Packing Dimensions	470 x 145 x 336 mm (W x D x H)
Net / Gross Weight	2,45 Kg / 3,05 Kg



VESA Mounting	75 x 75 mm / 100 x 100 mm Screws: M4, 4mm (Max), pitch 0.7
Display Protection	TP Module Protection Thickness 3,3±0.3 mm
Hardness / Transmittance	≥7H Toughened hard panel surface / ≥85%
IP Rating Level	IP 54 (Front), Water and Dust Protection *
Control	Auto, Power, (+), (-), Menu
LED Backlight life	15.000 hours
Accessory	Power supply; HDMI Cable (1.5m); USB Cable for Touch.
Certifications	CE, RoHS, REACH
On Screen Display	9 Languages
Color	9300, 7500, 6500, User Mode
Orientation	Landscape, Portrait, Face-Up

Supplier's Name	HANNspree
Model Name	HO161HTB
Energy Efficiency Class	A++
Screen Size (Centimetres)	39,60
Screen Size (Inches)	15,60
On mode power Consumption (W)	7
Annual Energy Consumption* (kWh)	9
Standby-mode Power Consumption (W)	0,121
Off-mode Power Consumption (W)	0,109
Screen Resolution	1920 x 1080

PART. NO.:  
HO 161 HTB




\* IP54: The IP Code classifies how resistant a device is to foreign objects and moisture.  
IP54 means that the monitor will operate in dusty conditions, and will resist splashing water.


**HANNSpree**

**HO 161 HTB**  
**15.6" Open Frame Touch Monitor**

Experts in **Display**



## HO 161 HTB 15.6" Open Frame Touch Monitor



Title	15.6 Inch Pure Flat Capacitive Touch Monitor Mechanical Diagram
-------	---