



1723L 17-inch LCD

Touchscreen Monitor



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1723L 17-inch standard format touchscreen monitor meets the durability and aesthetic requirements for a variety of high traffic retail and hospitality interactive solutions. The sleek, edge-to-edge glass design of the 1723L brings a clean, modern feel to any environment. The zero-bezel monitor is available in both black or white with Elo's industry-leading touch technologies, both providing a stable drift-free operation with outstanding image clarity, resolution and light transmission - for an accurate touch response and vivid images.

The 1723L has been designed for touch from the ground up, with such features as a spill-resistant sealing, adjustable height stand with tilting functionality, VESA mounting option, connectivity incorporated within the monitor (reducing the number of power bricks), and communication cables and side controls with lockout capability.

Available with dual touch IntelliTouch® zero-bezel surface acoustic wave (SAW) or 10-touch TouchPro™ PCAP touch technology

Integrated peripheral options include

- MSR
- Webcam
- RFID reader
- Customer-facing display

Integrated cable management

1723L 17-inch LCD Touchscreen Monitor

Specifications	
Model	1723L
Color	Black or white
Active Display Area	13.3" x 10.64" (337.92mm x 270.34mm)
Dimensions	15.43" x 8.24" x 14.20" (391.9mm x 209.4mm x 360.7mm)
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	17"
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Preset Video Timings	640 x 480 60Hz, 75Hz; 720 x 400 70Hz; 800 x 600 56Hz, 60Hz, 75Hz; 1024 x 768 60Hz, 75Hz; 1280 x 1024 60Hz, 75Hz
Number Of Colors	16.7 million
Number of Touches	Dual-touch and multi-touch
Brightness (Typical)	LCD Panel: 250 nits; TouchPro PCAP: 215 nits; IntelliTouch ZB: 225 nits
Response Time (Tr + Tf) (Typical)	5 msec
Viewing Angle (Typical)	Horizontal: ±70° or 140° total; Vertical: ±80° or 160° total
Contrast Ratio (Typical)	1000:1
Video	Analog VGA on Female DE-15 connector; Digital DVI on Female DVI-D, Dual-Link connector; Input Video Horizontal Sync frequency range: 31.5-80KHz; Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Speakers	2 x 2W internal speakers
Additional Ports	2 External USB Ports
Power	Monitor input power connector: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC ±5% (Note: This monitor is sold with an AC-DC power adapter.); Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (monitor + AC/DC adapter - Typical) - ON: 19.2W; SLEEP: 1.22W; OFF: 0.19W
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit; 3-hole threaded mounting on bottom of stand
Weight	Unpackaged: 11.46 lbs (5.2 kg); Packaged: 18.7 lbs (8.5 kg)
Shipping Dimensions	19.65" x 17.17" x 8.39" (499mm x 436mm x 213mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity (Non-Condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory Approvals and Declarations	C-Tick; cUL, IC; CCC; CE; VCCI; KCC, e-Standby; CoC; BSMI Mark; UL, FCC; CB; RoHS, China and RoHS, WEEE, IMERC
Warranty	3 years standard
MTBF	50,000 hours demonstrated
What's in the Box	QIG, Japan Class-B TM info sheet, User Manual CD, 50W Power Brick, power cable, IEC 60320-C13 to NA/EU plug, DVI-D cable, VGA cable (DE-15 male to DE-15 male), USB cable (Type A plug to Type B plug), audio cable, stand base assembly, filler plate

Ordering Information

Model	Part Number	Technology	Surface Treatment	Interface	Color	Availability
1723L	E785229	IntelliTouch ZB Dual Touch	Antiglare	USB	Black	Worldwide
	E924166	IntelliTouch ZB Dual Touch	Antiglare	USB	White	Asia-Pacific & Japan
	E683457	TouchPro PCAP	Antiglare	USB	Black	Worldwide
	E016808	TouchPro PCAP	Antiglare	USB	White	Worldwide

Optional Peripherals / Accessories

Part Number	Peripheral	Color
E628912	Magnetic stripe reader	Black
E617494	Magnetic stripe reader	White
E545740	Web Cam	Black
E196192	Web Cam	White
E326847	RFID Reader	Black
E663259	RFID Reader	White
E808749	0700L Mounting Bracket Kit	Black
E832504	0700L Mounting Bracket Kit	White

Extended Warranty Options

Part Number	Description
758588-000	1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
930057-000	2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
E67295-000	Elo advance unit replacement for touchmonitors

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
 Fax +1 408 597 8050
elosales.na@elotouch.com

Europe

Tel +32 (0)16 70 45 00
 Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
 Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
 Fax +1 305-931-0124
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17051AES00057

