

AXIS S9201 Mk II

All-in-one solution for optimal viewing

AXIS Camera Station S9201 Mk II Desktop Terminal is a compact all-in-one desktop terminal designed for optimal viewing of high-definition surveillance video where space is limited. The terminal is preloaded with AXIS Camera Station software to minimize installation time and complements Axis network video recorders to create a high performing surveillance workstation. AXIS S9201 Mk II has validated hardware and software components for optimal surveillance experience and includes three-year hardware warranty with on-site replacement service. AXIS S9201 Mk II includes a 22 inch monitor for system overview, as well as a universal keyboard and a computer mouse.

- > **Ease of installation**
- > **AXIS Camera Station software included**
- > **22 inch monitor included**
- > **Validated hardware**
- > **On-site replacement service**



AXIS S9201 Mk II

| | | | |
|-----------------------------|---|--|---|
| Processor | Intel® Core i3-8100 | Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) |
| Memory | 8 GB RAM | Approvals | IEC/EN/UL 60950-1 FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KN35, EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 50564, EN 62623, EAC, BSMI, NOM |
| Operating system | Microsoft® Windows® 10 Enterprise Operating system recovery: yes Operating system drive: 128 GB SSD | Dimensions | Monitor: 55 x 498 x 329 mm (2.15 x 19.6 x 12.9 in) Stand: 225 x 256 mm, adjustable height (8.9 x 10.1 in, adjustable height) |
| Video streaming | Built-in monitor Live view and playback: Up to 25 camera split views or 1 x 1080 camera view Supports up to 4K on external monitor | Weight | 7.4 kg (16 lb) |
| Graphic card | Intel® HD Graphics 630 | Included accessories | Keyboard (international/US), computer mouse, height adjustable stand |
| Power | 155 W (100 - 240 V AC, 50/60 Hz, 3 - 1.5 A) | Optional accessories | Axis joysticks and control boards For more accessories, see axis.com |
| Connectors | 4x USB 3.1 1x USB 3.1 Type-C 2x USB 2.0 1x Ethernet (RJ45) 1x DisplayPort™ 1.2 1x Universal audio jack 1x Audio line out 1x SD card reader | Warranty | Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty |
| Mounting option | VESA 100 x 100 mm (3 15/16 x 3 15/16 in) | Environmental responsibility: www.axis.com/environmental-responsibility | |
| Operating conditions | 0 °C to 35 °C (32 °F to 95 °F) Humidity 20–80% RH (non-condensing) | | |