

Product profile

SR61T

(SR61T1D, SR61T2D,
SR61THP, SR61TL)

Industrial Tethered
Scanner Family



The Intermec SR61T family of handheld barcode scanners offers a broad choice of linear imager, area imager and laser scanning options.

- **Ruggedized** – designed to maximize up time by withstanding 26 drops to concrete or steel from 2 m (6.5 foot), hot and cold temperature extremes, constant forklift vibration and windblown dust and rain.
- **Easy to use** – all models feature highly visible easy to use aimers that make spotting the bar code fast and efficient.
- **Ergonomic** – area imagers feature omni-directional bar code reading to eliminate orientation and improve operator efficiency.
- **Powerful** – 2D imagers feature VGA+ resolution image capture, real time video and 1D & 2D bar code scanning in the single multipurpose device spreading your investment over multiple uses.
- **Fast** – features USB 2.0 full speed interface to quickly transfer bar code data or images to the host application saving operator time.

- **High Performance** – the HP imager model offers superior motion tolerance and fast time to read. A combination of white illumination and red laser aimer provide this scanner with exceptional time to read performance, saving time reading linear and 2D codes.
- **Future proofed** – 2D imagers easily read linear, stacked, composite and matrix barcodes.

The Intermec SR61T handheld scanner family meets the needs of rugged applications in warehouse, distribution and industrial manufacturing, and also supports proof of delivery and point of service applications. Featuring high impact housing that is virtually impenetrable as well as a solid state design, the SR61T scanners exceed industrial and military standards, and can be counted on for use in harsh environments where dust, moisture or extreme temperatures are constants and production uptime is critical. If your enterprise requires data collection tools that are dependable then the SR61T is the product for you. With multiple scan options, including linear, area and standard range laser, SR61T scanners allow users to configure their scanner to meet the needs of their environment – whether this includes reading specific barcode symbologies or decoding poor quality or damaged

symbols. If reading bar codes quickly while in motion is critical to your application, then the SR61THP is the right choice for you. Its high performance exceptional time to decode will add efficiency to many data collection environments. The flexibility of the SR61T family of scanners also means customers can increase productivity while keeping costs down. This flexibility is demonstrated with the ability to interface with Intermec computers, printers and standard PCs. Additionally, users may connect to many host devices supporting multiple applications including inventory management, picking, shipping and receiving, cross docking, work-in-process, tool crib, and pallet tracking. To save time during deployment the SR61T family includes Intermec's EasySet™ software setup tool for quick and easy configuration and personalization of your scanner system. The SR61T family can improve many data capture applications by quickly decoding poor quality or damaged barcodes. The area imagers on board image capture and video function can remove the expense of separate digital image equipment often used to document and prove the condition of warehouse goods. Users can also quickly set security options, select beeper tones and volumes, specify good read and error read responses, and make many other customizations.

Physical Characteristics

Length: 19.4 cm (7.6 in) Width: 7.2 cm (2.8 in)
Height: 13.1 cm (5.2 in) Weight: 320 gm (11.2 oz)

Power Requirements

5 vdc, 1.7A

Connectivity

Connection to Intermeccomputers and printers.
Also connects to standard PCs.

Interfaces

RS232, USB 2.0 (HID Keyboard, Virtual Com Port, Video Class), Keyboard Wedge, Wand Emulation

Scan Engine Options

HP - High Performance Area Imager (EA30)
2D - Standard Area Imager (EA20x)
1D - Linear Imager (EV10)
L - Standard Range Laser (EL20)

Scan Range

Typical reading distances at 200 lux

Linear SR61T1D

Symbology	Density	Minimum Distance	Maximum Distance
Code 39	0.1 mm (3.8 mils)	10 cm (3.94 in)	14 cm (5.51 in)
	0.125 mm (5 mils)	9 cm (3.54 in)	17.5 cm (6.89 in)
	0.25 mm (10 mils)	5.5 cm (2.17 in)	26 cm (10.24 in)
	0.5 mm (20 mils)	4 cm (1.57 in)	35 cm (13.78 in)
EAN/UPC	1 mm (40 mils)	7.5 cm (2.95 in)	49 cm (19.29 in)
	0.33 mm (13 mils)	5.2 cm (2.05 in)	28.5 cm (11.22 in)

Laser SR61TL

Symbology	Density	Minimum Distance	Maximum Distance
Code 39	0.125 mm (5 mils)	10 cm (3.94 in)	19.5 cm (7.68 in)
	0.5 mm (20 mils)	6 cm (2.36 in)	85 cm (33.46 in)
	1.3 mm (51 mils)	41* cm (16.14 in)	150 cm (59.1 in)
EAN/UPC	0.33 mm (13 mils)	4.5 cm (1.77 in)	49 cm (19.29 in)

*Depends on symbology length and scan angle.

Asia Pacific Headquarters Office

Singapore

Intermec Technologies (S) Pte Ltd
151, Lorong Chuan,
#05-02A/03 (Lobby C),
New Tech Park,
Singapore 556741
Tel : +65 6303 2100
Fax : +65 6303 2199
www.intermec.com.sg

Malaysia

Suite L-8-11, Level-8, Wisma BU8,
No 11, Lebuhr Bandar Utama, PJU 6,
Petaling Jaya, 47800,
Selangor,
Malaysia
Tel : +603 7726 8730
Fax : +603 7727 8731

Thailand

Two Pacific Place,
Unit 1105,
142 Sukhumvit Road,
Klongtoey, Bangkok 10110,
Thailand
Tel : +662 653 2750
Fax : +662 653 2751

Australia

Intermec Technologies Australia
Pty. Ltd.
Level 4, 1-3 Atchison Street,
St. Leonards, NSW 2065,
Australia
Tel : +61 2 9330 4400
Fax : +61 2 9437 0240
www.intermec.com.au

Korea

Hong-Eun B/D Room 902,
824-22, Yeoksam-dong,
Gangnam-gu,
Seoul 135-934,
Korea
Tel : +82 2 552 2484
Fax : +82 2 552 2483

Hong Kong

Rm 3601 11/F,
AXA Centre,
151 Gloucester Road,
Wanchai,
Hong Kong
Tel : 852.3752 1906
Fax : 852.3013 9401

China

Beijing
1510A, 15th floor, South Tower,
Raycom Infotech Park C,
No.2 Science Institute South Road,
Beijing, 100190,
P.R. China
Tel : +86 10 5165 5922
Fax : +86 10 6583 4408

Shanghai

Unit B3, Floor 28, JuneYao
International Plaza,
No.789 Zhaojiangbang Rd,
Shanghai, 200032,
P.R. China
Tel : +86 21.6278 1090
Fax : +86 21.6278 1081

Shenzhen

Unit 1308, International Chamber of
Commerce Tower, Fu Hua Third Road,
Fu Tian Central District,
Shenzhen 518048,
P.R. China
Tel : +86 755.8831 2391
Fax : +86 755.8831 2396

China Toll Free: 400 6100 277
www.intermec.com.cn

2D SR61T2D

Symbology	Density	Minimum Distance	Maximum Distance
Code 39	0.15 mm (6 mils)	15.5 cm (6.10 in)	22 cm (8.66 in)
	0.2 mm (8 mils)	11.5 cm (4.53 in)	31 cm (12.20 in)
	0.25 mm (10 mils)	9 cm (3.54 in)	41 cm (16.14 in)
	0.5 mm (20 mils)	8 cm (3.15 in)	76 cm (29.92 in)
	1 mm (40 mils)	13 cm (5.12 in)	120 cm (47.24 in)
	EAN/UPC	0.33 mm (13 mils)	9 cm (3.54 in)
PDF417	0.17 mm (6.6 mils)	14.5 cm (5.71 in)	22 cm (8.66 in)
	0.25 mm (10 mils)	9 cm (3.54 in)	36 cm (14.17 in)
	0.38 mm (15 mils)	10 cm (3.94 in)	52 cm (20.47 in)
DataMatrix	.025 mm (10 mils)	13 cm (5.12 in)	29 cm (11.42 in)

2D SR61THP

Symbology	Density	Minimum Distance	Maximum Distance
Code 39	0.125 mm (5 mils)	8 cm (3.15 in)	14 cm (5.51 in)
	0.5 mm (20 mils)	7 cm (2.76 in)	46 cm (18.11 in)
	1 mm (40 mils)	9.5 cm (3.74 in)	70 cm (27.56 in)
	EAN/UPC	0.33 mm (13 mils)	6 cm (2.36 in)
PDF417	0.25 mm (10 mils)	5.5 cm (2.17 in)	26 cm (10.24 in)
	0.38 mm (15 mils)	6.5 cm (2.56 in)	36 cm (14.17 in)
DataMatrix	.025 mm (10 mils)	6 cm (2.36 in)	21 cm (8.27 in)

Supported Bar Code Symbologies

for 1D and Laser Models

Codabar; Codablock A*; Codablock F*;
Code 11; Code 39; Code 93/93i;
Code 128/GSI-128; EAN/UPC;
GSI Composite*; GSI DataBar Expanded*;
GSI DataBar Limited*;
GSI DataBar OmniDirectional*;
GSI DataBar Stacked*; Interleaved 2 of 5;
Matrix 2 of 5; Micro PDF417*;
MSI; PDF417*; Plessey; Standard 2 of 5; Telegen; TLC 39
*These symbologies are only available with SR61TL (laser scanner).

Supported Bar Code Symbologies

for 2D and HP Models

Australian Post; Aztec; BPO; Canada Post; Codabar;
Clodablock A; Codablock F; Code 11; Code 39;
Code 93/93i; Code 128/GSI-128; DataMatrix; Dutch
Post; EAN/UPC; GSI Composite; GSI DataBar;
Expanded; GSI DataBar Limited; GSI DataBar
Omni-Directional; GSI DataBar Stacked; Infomail
Intelligent mail; Interleaved 2 of 5; Japan Post;
Matrix 2 of 5; Maxicode; Micro PDF417;
MSI; Multicode; PDF417;
Planet; Plessey; Postnet; QR Code;
Standard 2 of 5; Sweden Post; Telegen; TLC 39

Environment


Operating Temperature: -20°C to +50°C (-4°F to +122°F)
Storage Temperature: -40°C to +70°C (-40°F to +158°F)
Humidity: 5% to 95% RH, Non-condensing
Shock: 2000G
Vibration: 8G from 10Hz to 500Hz, 2hr/axis, 3 axes
Rain and Dust Resistance: IP54
Drop Survival: 26 drops onto concrete or steel
surface from a height of 1.98 meters (6.5 feet)
Ambient light: Works in any lighting
conditions from 0 to 100,000 lux

Accessories

Desktop Holder
Wall Mount/Vehicle Holder
Hands Free Stand
Belt Holster
Dangle Suspension
Wrist Strap (Lanyard)

Regulatory Approvals

SR61THP & SR61TL & SR61T2D Laser Class 2 product;
SR61T1D Laser Class 1; CISPR 22 Class B; Part 15 of FCC
rules, Class B; CE Mark (EU) (EN 55024, EN 55022 Class
B, IEC 60950-1, IEC 60825-1); cULus (Canada and the
USA) (UL 60950-1); GS Mark (Germany) (EN 60950-1,
EN 60825-1); NOM (Mexico); C-TICK (Australia and New
Zealand) (AS/NZS 3548 based on CISPR22); CQC (China)



Copyright © 2011 Intermec Technologies Corporation.
All rights reserved. Intermec is a registered trademark
of Intermec Technologies Corporation. All other
trademarks are the property of their respective owners.
Printed by MG Digital Corp-015 02/11.

In a continuing effort to improve our products, Intermec
Technologies (S) Pte Ltd reserves the right to change
specifications and features without prior notice.

