

DS-D6022FN-B Indoor Wall-Mounted Digital Signage



The digital signage is used to broadcast information, release news, advertise products, etc., which is widely applicable to industry of entertainment, finance, traffic, etc.

- Plastic shell appearance, slim frame, and all-in-one design.
- Exquisite image, industrial A+ panel, auto-coloring and image-enhancing engine.
- Variable materials, static and dynamic materials, including the pictures, audio, video, scrolling subtitle, PDF, webpages, live video, number calling, pop-up pictures, etc.
- Flexible program schedule, free schedules and district play of multiple materials and variable play modes: play by day, play by week, play by loop, custom play, etc.
- Centralized management, remotely control and manage one screen or more screens, such as timed startup/shutdown, quick startup/shutdown, brightness/volume timed adjustment, and screenshot preview, remotely release programs and updates local (USB) programs.
- Organization permission, 5-level organization is available for managing materials, programs, terminals, and users, and support creating custom users, allocating permission for users according to user level, and permission templates.
- Multiple security safeguards, 3-level check of materials, programs and schedules to prevent mistake release, encryption of data in storage and transmission to prevent data tampering, and with no default password, users can activate and set initial password to guarantee the password safety.



▪ Specification


Model		DS-D6022FN-B
Display	Viewing Angle	178°(H)/178°(V)
	Contrast Ratio	3000:1
	Screen Size	21.5 inch
	Active Display Area	478.656 mm (H) × 260.28 mm (V)
	Backlight	ELED
	Pixel Pitch	0.24795 (H) mm × 0.24795 (V) mm
	Resolution	1920 × 1080@60 Hz
	Brightness	250 cd/m ²
	Color Depth	8 bit, 16.7 M
	Response Time	6.5 ms
	Color Gamut	72% NTSC
	Reliability	7 × 24 h
	Refresh Rate	60 Hz
Built-in System	Operation System	Android 8.1.0
	CPU	Cortex-A17, 4-core, main frequency 1.6 GHZ
	Memory	2 GB
	Built-in Storage	16 GB
Interface	Video & Audio Input	AUDIO IN × 1
	Video & Audio Output	AUDIO OUT × 1
	Network Interface	LAN × 1, Wi-Fi
	Data Transmission Interface	USB 2.0 × 2, TF Card × 1, BT4.0 × 2, Wi-Fi
Internal Function	Loudspeaker	2 × built-in speaker, 8 Ω 5 W
Power	Standby Consumption	≤ 10 W
	Input Voltage	100 to 240 VAC, 50/60 ± 3 Hz
	Power Consumption	≤ 40 W
Working Environment	Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Working Humidity	20% to 90% RH
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)

	Storage Humidity	5% to 90% RH
General	Material Type	DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, TS, FLV, WEBM, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF, MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG
	Mounting Type	Wall-Mounted
	Product Dimensions (W × H × D)	516.75 (W) × 320.03 (H) × 46.55 (D) mm (without wall-mounted backboard) (20.34" × 12.60" × 1.83") 516.75 (W) × 320.03 (H) × 53.55 (D) mm (with wall-mounted backboard) (20.34" × 12.60" × 2.11")
	Package Dimensions (W × H × D)	593 (W) × 434 (H) × 157 (D) mm (23.35" × 17.09" × 6.18")
	Net weight	3.03 Kg (6.68 lb)
	Gross weight	4.63 Kg (10.21 lb)
	Packing List	Wall-mounted backboard × 1, screws M3 × 6, power cord × 1, remote control × 1, battery × 2, screw package × 1


▪ **Available Model**

DS-D6022FN-B

Dimension



Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com