



FCS-5060 Version: 1

Fixed IP Network Camera, 2-Megapixel, two-way audio, 4X Optical Zoom, 802.3af PoE, Indoor/Outdoor

The LevelOne FCS-5060 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP66 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5060 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- Weatherproof IP66-rated housing
- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264/MJPEG
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Built-in infrared LEDs for night viewing up to 30m
- Digital input/output (1DI/1DO) for sensor and alarm
- Power support: PoE (IEEE 802.3af)
-
- 2.8-12 mm adjustable Vari-focal length for wide angle surveillance

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, Unicast

Image Sensor:

1/2.8" Progressive Scan CMOS

Connectors and Cabling:

Power connector

10/100Mbps RJ45 Ethernet interface

1Vp-p composite output (75 Ω/BNC)

I/O terminal block (1 DI/1 DO)

Audio:In/Out

**Button/Knob:**

Reset button

Lens:

2.8 - 12 mm @ F1.4, motorization LENS,Auto Iris

IR Cut Filter:

Yes

IR LED:

IR LEDs for illumination up to 30m

Shutter Time:

1/3s ~ 1/10,000s

Angle of View:

106°~35°

Video Compression:

H.264/MJPEG/H.264+

Resolution:

2-Megapixel(1920 x 1080)

Video Format:

MP4

Audio Compression:

G.711/G.722.1/G.726/MP2L2

Power Input:

PoE (IEEE 802.3af)

12V DC±10%

Power Consumption:

Max.5.5W(Max. 7.5 W with IR cut filter on)

Features

PoE:

PoE (IEEE 802.3af)

Security:

One-key reset, flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, anonymous access

Video:

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- AGC/AWB/AES

- Back Light Compensation (BLC)

- Wide Dynamic Range (WDR)120dB

- 3D Noise Reduction (3DNR)

- Flip & Mirror

- Rotate Mode

- Portrait Mode

- Privacy Mask

- Time Stamp and Text Caption Overlay

Image Layout:

Streaming: Up to 2 video streams

Motion Detection: 3 Detection Zones

Audio:

G.711/G.722.1/G.726/MP2L2

64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)

Performance

Number of Clients:

20

Data Transfer Rate:

10/100Mbps

Storage Capacity:

Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB

Frame Rate (fps):

50Hz: 25fps(1920 × 1080, 1280 × 960, 1280 × 720)

60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)

Minimum illumination:

0.01Lux @(F1.2,AGC ON), 0.014 Lux @(F1.4,AGC ON), 0 Lux with IR

Environment

Temperature (°C):

30 °C ~ 60 °C (-22 °F – 140 °F)

Humidity (Non-condensing):

Humidity 95% or less (non-condensing)

Deployment:

Cable Management Bracket for Wall/Ceiling Mount

Physical Specifications

Dimensions (W x D x H mm):

5×105×258.6 mm (3.74" × 4.13" × 10.18")

Weight (g):

1200

Color:

White

Approval and Compliance

EMI/EMS:

CE,FCC

Environmental Test:

Weather proof IP66-rated housing

Others:

ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI

Others

Operation Systems:

Windows 7/8/10/

Viewing Systems:

Above IE 9 browser

Order Information

FCS-5060



Package Contents

FCS-5060

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Optional Accessory



CAS-7303

Pole Mount Bracket, Clamping Range 2.6"-5"



CAS-7307

Corner Mount Bracket



CAS-7311

Junction box for Bullet Camera



CAS-7312

Power Intake Box for Bullet Camera

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.