

Data Sheet Fujitsu Display B22W-7 LED Display

Advanced display: 55.9 cm (22-inch) widescreen Best ergonomic and energy saving solutions for office applications

The Display B22W-7 LED offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Environment-friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Flexible connectivity with 4x USB, DisplayPort, DVI and Analog

Ready for remote inventory and administration tasks due to the DisplayView Manageability tools

Representative design with space saving front frame and smart details like discretely integrated speakers





























Technical details

C : 15 :	
Special features	/ in 1 Stand FCO hutton FCO Status LFD: 2 calors for 2 modes Divot 2//7 years Disabet/invitMIT Cuits
Francomic stand	4-in-1 Stand, ECO button, ECO Status LED: 3 colors for 3 modes, Pivot, 24/7 usage, DisplayView™ IT Suite
Ergonomic stand	/ in 1 Stand
Stand Joint adjust sange	4-in-1 Stand
Height adjust range	130 mm
Picture height over desk (min)	50 mm 90°
Rotation to portrait	
ilt angle	-5° / +35°
wivel angle	340°
Picture performance	THUED
anel and backlit	TN/LED
creen Surface Treatment	3H hard coating, Anti-glare
ontrast - typical	1000:1
ontrast - advanced	20,000,000:1
tesponse time typical	5 ms
/iewing angle (h/v) - typical	170°/170° CR5:1
olor performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2
ize and resolution	
spect ratio	16:10
iagonal Size	55.9 cm (22-inch)
esolution (native)	1680 x 1050 pixel (recommended)
esolution (interpolated)	1440 x 900 pixel, 1280 x 1024 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
icture size	474 x 296 mm
ixel Pitch	0.282 mm
requencies	
Iorizontal	30 - 82 kHz
'ertical	56 - 76 Hz
requencies - bandwidth	165 Mhz
Connectivity	
DisplayPort	1 x DisplayPort
VI	1 x DVI (HDCP)
'GA/D-SUB	1 x D-SUB
audio signal output	3.5 mm stereo phone jack for head phone
audio signal input	3.5 mm stereo phone jack
audio sound output	2 x 1.5 W
ISB downstream	4 x USB 2.0
ISB upstream	1 x USB
ase-of-use menu	
anguages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
olor	sRGB, 6500K, 7500K, 9300K, Native, Custom Color (R,G,B)
mage adjust	Clock, Phase, H-Position, V-Position, Expansion
udio	Mute, Volume
nformation	Model name, S/N, Resolution/mode, Signal input
Setup	Input select, Language, DDC-CI, OSD-Timeout, Factory recall
Power consumption (typical)	
Soft switch off	0.2 W
Power save mode	0.2 W 0.3 W
rowei Save Illoue	U.J YY

Operating with EPA settings	17 W
Operating maximum brightness	22 W
Power supply display	integrated
Power notes	without sound, without USB;
Electrical values	minote sound, minote oso,
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	<u>'</u>
Europe	EN 60950, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Model	B22W-7
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cUL
Australia/New Zealand	C-Tick (planned)
Japan Japan	VCCI
South Korea	KC (planned)
Argentina	TÜV-S
China	CCC (planned)
Saudi Arabia	SASO
Global	TCO Displays 6.0, ENERGY STAR® 6.0 in progress, EPEAT® Gold (dedicated regions) (planned), ISO9241-307 (Pixel fault
diodai	class I)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Quality and Reliability	ntp.//globalsp.ts.htgltsa.com/sites/certificates
MTBF (demonstrated)	70000 h
Dimensions / Weight / Environmental	7000011
Dimension without stand (W x D x H)	514 x 65 x 346 mm
Dimension without staild (M X D X D)	20.24 x 2.56 x 13.62 inch
Dimension with stand (W x D x H)	514 x 199 x 367 mm
	20.24 x 7.83 x 14.45 inch
Weight (packed)	7.5 kg
	16.53 lbs
Weight (unpacked)	6.0 kg
mengine (emperince)	13.23 lbs
Weight (Monitor only)	3.4 kg
	7.50 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Miscellaneous	3 33 6(1.7 33 1)
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
Package content	y -
Display delivered accessories	DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m , Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable
	for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1472-V140
Country specific order code	BDL:K1472V140-UK - with UK power cable, mandatory for Arabian countries BDL:K1472V140-CHN - with China power cable and CEL, mandatory for China BDL:K1472V140-ID - with Import label, mandatory for Indonesia BDL:K1472V140-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
EAN Code	4051554619831
Warranty	
Standard Warranty	3 years (depending on country)
	- (₁ ₁ ₁)

Warranty	
Service level	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu Display B22W-7 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Display B22W-7 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-07-29 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms Copyright © Fujitsu Technology Solutions