

# Data Sheet

## FUJITSU Server PRIMERGY RX2540 M4 Dual Socket 2U Rack Server

The data center standard without compromise

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as hyper-converged scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

FUJITSU Server PRIMERGY RX rack systems are versatile rack-optimized servers providing best-in-class performance and energy efficiency, and thus form the "standard" in each data center. PRIMERGY RX servers deliver more than 20 years of development and production know-how resulting in extremely low failure rates below market average, and lead to continuous operations and outstanding hardware availability.

### PRIMERGY RX2540 M4

The FUJITSU Server PRIMERGY RX2540 M4 sets higher standards for usability, scalability and cost-efficiency. It is a 2U dual-socket rack server ideal for running enterprise applications, collaboration and messaging workloads as well as traditional databases. Plus, it substantially simplifies carrying out infrastructure-related tasks like server virtualization and consolidation. As one of the key innovations, versatile performance is guaranteed by a new generation of processors. The PRIMERGY RX2540 M4 can be equipped with two of the latest Intel® Xeon® Processor Scalable

Family CPUs with up to 28 cores each. Along with DDR4 memory technology with up to 3TB it boosts application performance to be able to cope with the increasing data growth and shortens time to business results. NV-DIMMs will be supported from mid-2018 on. The modular design of the server offers excellent expandability with up to 28 disk drives, high storage density, up to 8 PCIe Gen 3 I/O expansion slots. A variety of onboard DynamicLoM options, plus its dual-port embedded LAN meet future requirements, cost-optimized. The PRIMERGY RX2540 M4 comes with two redundant hot-plug power supply units, offering up to 96% energy efficiency. The Cool-safe® Advanced Thermal Design allows for operation in ambient temperatures of up to 45 °C/104 °F. Both these features in line help to reduce operational expenses.



# Features & Benefits

| Main Features   | Benefits  |
|---|---|
| <p><b>Versatile Performance for any computing need</b></p> <ul style="list-style-type: none"> <li>■ Intel® Xeon® Processor Scalable Family CPUs with up to 28 cores relying on Intel® UltraPath Interconnect for an increased data rate between the CPUs</li> <li>■ Up to 3,072 GB DDR4 memory with 2,666 MHz (24 DIMM slots), NV-DIMM (coming mid-2018)</li> <li>■ 8x PCIe Gen3 slots</li> </ul> <p><b>Enhanced Features for enhanced Computing</b></p> <ul style="list-style-type: none"> <li>■ Onboard LAN via OCP for basic LAN, DynamicLoM for extended requirements</li> <li>■ Mix&amp;Match storage drive bays: Ideal scalability of either up to 12x 3.5-inch or up to 24x 2.5-inch HDD/SSD/PCIe SSD+ an additional rear option of 4x 2.5-inch drives</li> <li>■ 2x internal M.2 devices support for hypervisor installations</li> <li>■ Power supply units with 96% energy efficiency</li> <li>■ Fujitsu's Cool-safe® Advanced Thermal Design for higher ambient temperatures in the data center</li> <li>■ Optional liquid cooled base unit</li> <li>■ Up to 2x GPGPU support within one system</li> </ul> <p><b>Foundation for Trust and Security</b></p> <ul style="list-style-type: none"> <li>■ Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control</li> <li>■ BIOS, firmware and selected software are updated free of charge</li> <li>■ TPM2.0 modules and latest operating system support</li> </ul> <p><b>Simplified management</b></p> <ul style="list-style-type: none"> <li>■ iRMC S5 comes with new interactive web UI and conforms to Redfish providing unified API support for heterogeneous environment</li> <li>■ RAID Controller embedded onboard</li> </ul> | <ul style="list-style-type: none"> <li>■ Ready for the future and data growth scenarios with the performance of two processors – marking the standard of tomorrow with an increase in computing power</li> <li>■ DDR4 memories with higher bandwidth and lower consumption are the enabler; optimized for virtualization and clouds, data centers and high performance computing</li> <li>■ Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa.</li> </ul> <p>■ The right Ethernet connection for all: Basic via onboard LAN, extended with DynamicLoM guarantees the highest flexibility to integrate the server into existing infrastructures – now and in future without overhauling the existing infrastructure</p> <ul style="list-style-type: none"> <li>■ Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa.</li> <li>■ Not only “greener”, also less expensive over time: Highly efficient hot-plug power supplies save energy costs and make it easy to maintain the running system and ensure industry-leading uptime</li> <li>■ Higher ambient temperatures lead to lower costs for cooling the data center</li> <li>■ Less noise, latest technology to cool processors and memory directly where the heat is being generated</li> <li>■ Optimal for VDI, CAD or future technologies such as Artificial Intelligence of Virtual Reality applications</li> </ul> <ul style="list-style-type: none"> <li>■ Lifecycle investment protection</li> <li>■ The comprehensive tools of the Fujitsu ServerView Suite eases the administrators life</li> <li>■ Hardware and Software driven security features are very important in a fast-paced world, especially considering cybercrime.</li> </ul> <ul style="list-style-type: none"> <li>■ Optimized for both: data centers and SMEs can now rely on latest generation iRMC S5 increasing security and server admin productivity</li> <li>■ RAID support for the most common configurations is conveniently embedded on the system board and does not require a dedicated controller</li> </ul> |

# Technical details

## PRIMERGY RX2540 M4

|                            |                         |                                 |                            |                           |                         |
|----------------------------|-------------------------|---------------------------------|----------------------------|---------------------------|-------------------------|
| Base unit                  | PRIMERGY RX2540 M4 LFF  | PRIMERGY RX2540 M4 LFF          | PRIMERGY RX2540 M4 SFF     | PRIMERGY RX2540 M4 SFF    | PRIMERGY RX2540 M4 SFF  |
| Housing types              | Rack                    | Rack                            | Rack                       | Rack                      | Rack                    |
| Storage drive architecture | 4x 3.5-inch SAS/SATA    | max. 12x 3.5-inch SAS/SATA/PCIe | 16x 2.5-inch SAS/SATA/PCIe | 8x 2.5-inch SAS/SATA/PCIe | 24x 2.5-inch SAS/SATA   |
| Power supply               | Hot-plug                | Hot-plug                        | Hot-plug                   | Hot-plug                  | Hot-plug                |
| Product Type               | Dual Socket Rack Server | Dual Socket Rack Server         | Dual Socket Rack Server    | Dual Socket Rack Server   | Dual Socket Rack Server |

## Mainboard

|                             |  |
|-----------------------------|--|
| Mainboard type              | D3384  |
| Chipset                     | Intel® C624                                    |
| Processor quantity and type | 1 - 2 x Intel® Xeon® Processor Scalable Family |
| Mainboard type              | D3384  |
| Processor quantity and type | 1 - 2  |

|                                      |   |
|--------------------------------------|---|
| <b>Intel® Xeon® Bronze Processor</b> | Intel® Xeon® Bronze 3104 processor (6C nHT, 1.70 GHz, TLC: 8.25 MB, Turbo: 1.70 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.30 GHz, AVX Turbo 1.30 GHz) |
|                                      | Intel® Xeon® Bronze 3106 processor (8C nHT, 1.70 GHz, TLC: 11 MB, Turbo: 1.70 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.30 GHz, AVX Turbo 1.30 GHz)   |

|                                      |   |
|--------------------------------------|---|
| <b>Intel® Xeon® Silver Processor</b> | Intel® Xeon® Silver 4108 processor (8C, 1.80 GHz, TLC: 11 MB, Turbo: 2.10 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.30 GHz, AVX Turbo 1.30 GHz)     |
|                                      | Intel® Xeon® Silver 4110 processor (8C, 2.10 GHz, TLC: 11 MB, Turbo: 2.40 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.70 GHz, AVX Turbo 2.10 GHz)     |
|                                      | Intel® Xeon® Silver 4112 processor (4C, 2.60 GHz, TLC: 8.25 MB, Turbo: 2.90 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 2.20 GHz, AVX Turbo 2.60 GHz)   |
|                                      | Intel® Xeon® Silver 4114 processor (10C, 2.20 GHz, TLC: 13.75 MB, Turbo: 2.50 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.20 GHz) |
|                                      | Intel® Xeon® Silver 4116 processor (12C, 2.10 GHz, TLC: 16.5 MB, Turbo: 2.40 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.70 GHz, AVX Turbo 2.10 GHz)  |

**Intel® Xeon® Gold Processor**

|  |
|--|
| Intel® Xeon® Gold 5115 processor (10C, 2.40 GHz, TLC: 13.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.40 GHz)   |
| Intel® Xeon® Gold 5118 processor (12C, 2.30 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,400 MHz, 105 W, AVX Base 1.90 GHz, AVX Turbo 2.30 GHz)   |
| Intel® Xeon® Gold 5120 processor (14C, 2.20 GHz, TLC: 19.25 MB, Turbo: 2.60 GHz, 10.4 GT/s, Mem bus: 2,400 MHz, 105 W, AVX Base 1.80 GHz, AVX Turbo 2.20 GHz)  |
| Intel® Xeon® Gold 5122 processor (4C, 3.60 GHz, TLC: 16.5 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 105 W, AVX Base 3.30 GHz, AVX Turbo 3.60 GHz)    |
| Intel® Xeon® Gold 6126 processor (12C, 2.60 GHz, TLC: 19.25 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)  |
| Intel® Xeon® Gold 6128 processor (6C, 3.40 GHz, TLC: 19.25 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 115 W, AVX Base 2.90 GHz, AVX Turbo 3.60 GHz)   |
| Intel® Xeon® Gold 6130 processor (16C, 2.10 GHz, TLC: 22 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)     |
| Intel® Xeon® Gold 6132 processor (14C, 2.60 GHz, TLC: 19.25 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)  |
| Intel® Xeon® Gold 6134M processor (8C, 3.20 GHz, TLC: 24.75 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 130 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz)  |
| Intel® Xeon® Gold 6134 processor (8C, 3.20 GHz, TLC: 24.75 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 130 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz)   |
| Intel® Xeon® Gold 6136 processor (12C, 3.00 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 2.60 GHz, AVX Turbo 3.30 GHz)  |
| Intel® Xeon® Gold 6138 processor (20C, 2.00 GHz, TLC: 27.5 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.30 GHz)   |
| Intel® Xeon® Gold 6140M processor (18C, 2.30 GHz, TLC: 24.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz) |
| Intel® Xeon® Gold 6140 processor (18C, 2.30 GHz, TLC: 24.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)  |
| Intel® Xeon® Gold 6142M processor (16C, 2.60 GHz, TLC: 22 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)    |
| Intel® Xeon® Gold 6142 processor (16C, 2.60 GHz, TLC: 22 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)     |
| Intel® Xeon® Gold 6144 processor (8C, 3.50 GHz, TLC: 24.75 MB, Turbo: 4.10 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 150 W, AVX Base 2.80 GHz, AVX Turbo 3.50 GHz)   |
| Intel® Xeon® Gold 6146 processor (12C, 3.20 GHz, TLC: 24.75 MB, Turbo: 3.90 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 165 W, AVX Base 2.60 GHz, AVX Turbo 3.30 GHz)  |
| Intel® Xeon® Gold 6148 processor (20C, 2.40 GHz, TLC: 27.5 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)   |
| Intel® Xeon® Gold 6150 processor (18C, 2.70 GHz, TLC: 24.75 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 2.30 GHz, AVX Turbo 3.00 GHz)  |
| Intel® Xeon® Gold 6152 processor (22C, 2.10 GHz, TLC: 30.25 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)  |
| Intel® Xeon® Gold 6154 processor (18C, 3.00 GHz, TLC: 24.75 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 200 W, AVX Base 2.60 GHz, AVX Turbo 3.30 GHz)  |

|   |  |
|---|--|
| <b>Intel® Xeon® Platinum Processor</b>  | Intel® Xeon® Platinum 8153 processor (16C, 2.00 GHz, TLC: 22 MB, Turbo: 2.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.00 GHz)   |
|   | Intel® Xeon® Platinum 8160M processor (24C, 2.10 GHz, TLC: 33 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)  |
|   | Intel® Xeon® Platinum 8160 processor (24C, 2.10 GHz, TLC: 33 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)   |
|   | Intel® Xeon® Platinum 8164 processor (26C, 2.00 GHz, TLC: 35.75 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.60 GHz, AVX Turbo 2.30 GHz)  |
|   | Intel® Xeon® Platinum 8168 processor (24C, 2.70 GHz, TLC: 33 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 205 W, AVX Base 2.30 GHz, AVX Turbo 3.00 GHz)   |
|   | Intel® Xeon® Platinum 8170M processor (26C, 2.10 GHz, TLC: 35.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)   |
|   | Intel® Xeon® Platinum 8170 processor (26C, 2.10 GHz, TLC: 35.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)  |
|   | Intel® Xeon® Platinum 8176M processor (28C, 2.10 GHz, TLC: 38.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)  |
|   | Intel® Xeon® Platinum 8176 processor (28C, 2.10 GHz, TLC: 38.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)   |
|   | Intel® Xeon® Platinum 8180M processor (28C, 2.50 GHz, TLC: 38.5 MB, Turbo: 3.20 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 205 W, AVX Base 1.70 GHz, AVX Turbo 2.30 GHz)  |
|   | Intel® Xeon® Platinum 8180 processor (28C, 2.50 GHz, TLC: 38.5 MB, Turbo: 3.20 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 205 W, AVX Base 1.70 GHz, AVX Turbo 2.30 GHz)   |
| <b>Memory slots</b>                     | 24 (12 DIMMs per CPU, 6 channels with 2 slots per channel)   |
| <b>Memory slot type</b>                 | DIMM (DDR4)  |
| <b>Memory capacity (min. - max.)</b>    | 8 GB - 3072 GB   |
| <b>Memory protection</b>                | Advanced ECC<br>Memory Scrubbing<br>SDDC<br>Rank sparing memory support<br>Memory Mirroring support  |
| <b>Memory notes</b>                     | Memory Mirroring with identical modules in both channel pairs of a bank (6 modules per bank), Rank sparing or Performance Mode with identical modules in all six channels (6 modules per bank).  |
| <b>Memory options</b>                   | 8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 1Rx4<br>8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx8<br>16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 1Rx4<br>16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx4<br>16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx8<br>32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx4<br>64 GB (1 module(s) 64 GB) DDR4 3DS, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 4Rx4<br>64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, LRDIMM, 4Rx4<br>128 GB (1 module(s) 128 GB) DDR4 3DS, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 8Rx4 |
| <b>Interfaces</b>                       |  |
| <b>USB 3.0 ports</b>                    | 5 x USB 3.0 (2x front, 2x rear, 1x internal) - for base units with max. drives count: 1x USB 2.0 front only  |
| <b>Graphics (15-pin)</b>                | 2 x VGA (thereof 1x front optional)  |
| <b>Serial 1 (9-pin)</b>                 | 1 x serial RS-232-C optional, usable for iRMC or system or shared  |
| <b>Management LAN (RJ45)</b>            | 1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s)<br>Management LAN traffic can be switched to shared onboard LAN controller port, speed and connector is related to installed interface card.  |
| <b>Onboard or integrated Controller</b> |  |
| <b>RAID controller</b>                  | All hardware storage controller options are described under Components<br>For dedicated base units front AND rear storage drives may be connected to a single controller. Please see SystemArchitect for configuration options and restrictions.   |
| <b>SATA Controller</b>                  | Intel® C624, 1 x SATA channel for ODD  |

**Onboard or integrated Controller**

|                               |   |
|-------------------------------|---|
| LAN Controller                | Intel® C624<br>2 x 1Gbit/s onboard<br>Optional DynamicLoM OCP adaptors:<br>4 x 1 Gbit/s Ethernet (RJ45)<br>2 x 10 Gbit/s Ethernet (RJ45)<br>2 x 10 Gbit/s SFP+<br>4 x 10 Gbit/s SFP+<br>All supported features are described in relevant system configurator.<br>PXE-Boot via LAN from PXE server, iSCSI / FCoE boot (also diskless). |
| Remote management controller  | Integrated Remote Management Controller (iRMC S5, 1,024 MB attached memory incl. graphics controller)<br>IPMI 2.0 compatible  |
| GPU / coprocessor             | GFX/GPU support for dedicated base units. Please see relevant SystemArchitect for details and restrictions.   |
| Onboard controller notes      | Onboard 8x S-ATA 6Gbit/s RAID Controller (RAID 0,1) for up to 8x S-ATA drives available.  |
| Trusted Platform Module (TPM) | Infineon / TPM 1.2 or TPM 2.0 module; TCG compliant (option)  |

**Slots**

|                     |  |
|---------------------|--|
| PCI-Express 3.0 x8  | 3 x Low profile (2nd processor required for slot 4)  |
| PCI-Express 3.0 x16 | 3 x Low profile (2nd processor required for slot 5 and 6)  |
| Slot Notes          | One PCIe Gen3 x8 slot may be occupied with a Modular RAID controller if configured.<br>Important: 3 PCIe slots are supported with the first processor. 6 PCIe slots are supported with two processors.<br>PCIe riser card options can expand number of slots by two (max. 8 in total) and support max. 4 full height slots.<br>Possible slot length described in relevant system configurator. |

**Drive bays**

|                         |   |
|-------------------------|---|
| Storage drive bays      | 3.5-inch or 2.5-inch hot-plug SAS/SATA                          |
| Accessible drive bays   | 1 x 5.25/0.4-inch for CD-RW/DVD                                 |
| Notes accessible drives | All possible options described in relevant system configurator. |
| Optional hard disk bays | 4x 2.5-inch hot-plug SAS/SATA rear option                       |

**Drive bays (Base unit specific)**

|                            |                                 |                                 |                                 |                                 |                                 |
|----------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| Storage drive bays         | 4 x 3.5-inch hot-plug SAS/SATA  | 12 x 3.5-inch hot-plug SAS/SATA | 16 x 2.5-inch hot-plug SAS/SATA | 8 x 2.5-inch hot-plug SAS/SATA  | 24 x 2.5-inch hot-plug SAS/SATA |
| Accessible drive bays      | 1 x 5.25/0.4-inch for CD-RW/DVD |                                 | 1 x 5.25/0.4-inch for CD-RW/DVD | 1 x 5.25/0.4-inch for CD-RW/DVD |                                 |
| Optional accessible drives | ODD 5.25" possible              | ODD 5.25" NOT possible          | ODD 5.25" possible              | ODD 5.25" possible              | ODD 5.25" NOT possible          |

**General system information**

|                   |                      |
|-------------------|----------------------|
| Number of fans    | 6                    |
| Fan configuration | redundant / hot-plug |
| Fan notes         | 3x2 redundant        |

**Operating panel**

|                   |  |
|-------------------|--|
| Operating buttons | On/off switch<br>Reset button<br>NMI button<br>ID button   |
| Status LEDs       | System status (orange / yellow)<br>Identification (blue)<br>Hard disks access (green)<br>Power (amber / green)<br>At system rear side:<br>System status (orange / yellow)<br>Identification (blue)<br>LAN connection (green)<br>LAN speed (green / yellow) |

**BIOS**

|                      |  |
|----------------------|--|
| <b>BIOS features</b> | UEFI compliant<br>Legacy BIOS compatibility customer configuration option<br>Secure boot support<br>ROM based setup utility<br>GPT support for boot drives larger than 2.2 TB<br>Memory Redundancy support (Mirroring, Sparing)<br>IPMI support<br>Recovery BIOS<br>BIOS settings save and restore<br>Local BIOS update from USB device<br>Online update tools for main Linux versions<br>Local and remote update via ServerView Update Manager<br>IPv4/IPv6 remote PXE & iSCSI boot support |
|----------------------|--|

**Operating Systems and Virtualization Software**

|   |   |
|---|---|
| <b>Certified or supported operating systems and virtualization software</b> | Microsoft® Hyper-V Server 2016<br>Microsoft® Windows Server® 2016 Datacenter<br>Microsoft® Windows Server® 2016 Standard<br>Microsoft® Windows Server® 2016 Essentials<br>Microsoft® Windows Storage Server 2016 Standard<br>Microsoft® Hyper-V Server 2012 R2<br>Microsoft® Windows Server® 2012 R2 Datacenter<br>Microsoft® Windows Server® 2012 R2 Standard<br>Microsoft® Windows Server® 2012 R2 Essentials<br>Microsoft® Windows Storage Server 2012 R2 Standard<br>VMware vSphere™ 6.5<br>VMware vSphere™ 6.0<br>SUSE® Linux Enterprise Server 12<br>Red Hat® Enterprise Linux 7<br>Red Hat® Enterprise Linux 6<br>Oracle® Linux 7<br>Univention Corporate Server 4 |
| <b>Operating system release link</b>  | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>   |
| <b>Operating system notes</b>   | Support of other Linux derivatives on demand  |

**Server Management**

|                                      |  |
|--------------------------------------|--|
| <b>Standard</b>                      | <ul style="list-style-type: none"> <li>ServerView Suite (Deploy) <ul style="list-style-type: none"> <li>ServerView Installation Manager</li> <li>ServerView Scripting Toolkit</li> </ul> </li> <li>ServerView Suite (Control) <ul style="list-style-type: none"> <li>ServerView Operations Manager (incl. PDA and ASR &amp; R)</li> <li>ServerView Agents and CIM provider</li> <li>ServerView Agentless Management</li> <li>ServerView System Monitor</li> <li>SVOM- Event Manager</li> <li>ServerView RAID Manager</li> <li>SVOM- Threshold Manager</li> <li>Power Monitor (monitoring the Power Consumption)</li> <li>Power Management (iRMC)</li> <li>Storage Management (server) with SVOM/SV-RAID</li> </ul> </li> <li>ServerView Suite (Maintain) <ul style="list-style-type: none"> <li>iRMC S5 (Remote Management)</li> <li>System Update Manager (BIOS, Firmware, Windows Drives and SV Agents)</li> <li>Performance management (SVOM)</li> <li>Asset Management</li> <li>Primecollect</li> <li>Customer Self Service</li> <li>Online Diagnostics</li> </ul> </li> <li>ServerView Suite (Integrate) <ul style="list-style-type: none"> <li>ServerView Integration packs for MS System Center, VMware vCenter, VMware vRealize, Nagios, and HP SIM</li> </ul> </li> </ul> |
| <b>Option</b>                        | <ul style="list-style-type: none"> <li>ServerView Suite (Maintain) <ul style="list-style-type: none"> <li>ServerView eLCM</li> <li>iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media</li> </ul> </li> <li>ServerView Suite (Dynamize) <ul style="list-style-type: none"> <li>ServerView Virtual IO Manager (SVIOM)</li> <li>Resource Orchestrator- Cloud edition</li> <li>Resource Orchestrator- virtual edition</li> </ul> </li> </ul>   |
| <b>Server Management notes</b>       | Regarding dependencies for ServerView Suite software products see dedicated product data sheets.   |
| <b>Dimensions / Weight</b>           |  |
| <b>Rack (W x D x H)</b>              | 482.4 mm (Bezel) / 445 mm (Body) x 770 x 86.6 mm   |
| <b>Mounting Depth Rack</b>           | 740 mm   |
| <b>Height Unit Rack</b>              | 2 U  |
| <b>19" rackmount</b>                 | Yes  |
| <b>Mounting Cable depth rack</b>     | 200 mm (1,000 mm Rack recommended)   |
| <b>Weight</b>                        | up to 25 kg  |
| <b>Weight notes</b>                  | Actual weight may vary depending on configuration  |
| <b>Rack integration kit</b>          | Rack integration kit as option   |
| <b>Environment</b>                   |  |
| <b>Operating ambient temperature</b> | 5 - 45 °C (41 - 113 °F)  |
| <b>Operating temperature note</b>    | Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. For detailed information see relevant system configurator.<br>Ambient temperature limitation may differ for liquid cooled models. Please refer to the SystemArchitect for detailed information.  |
| <b>Operating relative humidity</b>   | 10 - 85 % (non condensing)   |
| <b>Operating environment</b>         | FTS 04230 – Guideline for Data Center (installation specification)   |
| <b>Operating environment link</b>    | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>  |
| <b>Noise emission</b>                | Measured according to ISO 7779 and declared according to ISO 9296  |
| <b>Sound pressure (LpAm)</b>         | Typical noise : 43 dB(A) (idle) / 43 dB(A) (operating)   |
| <b>Sound power (LWAd; 1B = 10dB)</b> | Typical noise : 6.1 B (idle) / 6.0 B (operating)   |
| <b>Noise notes</b>                   | Noise emissions depends on operation modes, system configuration and ambient temperature.<br>Typical hardware configuration which is the base for measurement according to ISO 7779: 2x PSU 450W. 2x CPU Xeon 85W, 4x RAM 16GB, 2x HDD 500GB SATA, 6x LAN 1 Gbit/s   |



| <b>Electrical values</b>            |  |
|-------------------------------------|--|
| Power supply configuration          | 1 x hot-plug power supply or 2x hot-plug power supply for redundancy   |
| Hot-plug power supply redundancy    | Optional   |
| Active power (max. configuration)   | 715 W  |
| Apparent power (max. configuration) | 753 VA   |
| Heat emission (max. configuration)  | 2574.0 kJ/h (2439.7 BTU/h)   |
| Rated current max.                  | 7.68 A (100 V) / 2.98 A (240 V)  |
| Active power note                   | To estimate the power consumption of different configurations use the Power Calculator of the System Architect: <a href="http://configurator.ts.fujitsu.com/public/">http://configurator.ts.fujitsu.com/public/</a>  |
| Power supply                        | 450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz<br>800W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz<br>800W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz<br>1200W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz; 110V range: 1000W, less than 110V: 900W<br>800W hot-plug, 94% (Platinum efficiency) –48V DC voltage |
| Power supply notes                  | Power Safeguard adapts system performance in case the power requirements exceeds supply limits.<br>!96% Titanium Power supply unit is only released for 200-240V   |

| <b>Compliance</b>     |   |
|-----------------------|---|
| Global                | CB<br>RoHS (Substance limitations in accordance with global RoHS regulations)<br>WEEE (Waste electrical and electronic equipment)   |
| Germany               | GS  |
| Europe                | CE  |
| USA/Canada            | CSAc/us<br>FCC Class A<br>ICES-003 / NMB-003 Class A  |
| Japan                 | VCCI:V3 Class A + JIS 61000-3-2   |
| Russia                | EAC   |
| South Korea           | KC  |
| China                 | CCC (planned)   |
| Australia/New Zealand | RCM   |
| Taiwan                | BSMI  |
| India                 | BIS R41004006   |
| Compliance link       | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>   |
| Compliance notes      | There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.<br>* Warning:<br>This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures. |

## Components

|                       |  |
|-----------------------|--|
| <b>Backup Drives</b>  | LTO5HH Ultrium, 1,500 GB, 140 MB/s, half height, SAS 6Gb/s                 |
|                       | LTO6HH Ultrium, 2,500 GB, 160 MB/s, half height, SAS 6Gb/s                 |
|                       | LTO7HH Ultrium, 2,500 GB, 300 MB/s, half height, SAS 6Gb/s                 |
|                       | RDX Drive, 320 GB, 500 GB, 1 TB, 25 MB/s, half height, USB 3.0             |
| <b>Optical drives</b> | Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I |
|                       | DVD Super Multi ultra slim, (8x DVD; 24x CD), ultraslim, SATA I            |

## Hard disk drives

|   |
|---|
| HDD SATA, 6 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical |
| HDD SATA, 6 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical  |
| HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical  |

## Hard disk drives

|   |
|---|
| HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise            |
| HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED |
| HDD SAS, 12 Gb/s, 450 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise            |
| HDD SAS, 12 Gb/s, 450 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise            |
| HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED |
| HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED   |
| HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical |
| HDD SAS, 12 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  |
| HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED    |
| HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  |
| HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical        |
| HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  |
| HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical        |
| HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical  |
| HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical  |
| HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical  |
| HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED |
| HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise            |
| HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise      |
| HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED |
| HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical        |
| HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical  |
| HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical  |



|  |  |
|--|--|
|  | SSD M.2 SATA, 6 Gb/s, 150 GB, non hot plug, enterprise, 1.5 DWPD (Drive Writes Per Day for 5 years)  |
|  | SSD M.2 SATA, 6 Gb/s, 150 GB, non hot plug, enterprise   |
| <b>SCSI / SAS Controller</b>           | LSI PSAS CP400e LP SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8<br>Fujitsu PSAS CP400i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8<br>Fujitsu PSAS CP400e FH SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8   |
| <b>RAID Controller</b>                 | Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s (coming Q1/2018) 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516<br>Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108<br>Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108<br>Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108<br>Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support  |
| <b>Fibre Channel controller</b>        | Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style<br>Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style<br>Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style<br>Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style<br>Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style<br>Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style<br>Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style<br>Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style   |
| <b>Communication, Network</b>          | Converged Network Adapter 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Emulex )<br>Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 10Gbit/s Eth (RJ45) ( Emulex )<br>Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 RJ45 ( Intel® )<br>Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Emulex )<br>Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )<br>Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )<br>Ethernet Ctrl. 4 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )<br>Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )<br>InfiniBand HCA 1 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )<br>InfiniBand HCA 1 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed ( Mellanox )<br>InfiniBand HCA 2 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )<br>InfiniBand HCA 2 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed ( Mellanox )<br>Interface modul for Dynamic LoM 2 x 10 Gbit/s RJ45 ( Intel® )<br>Interface modul for Dynamic LoM 2 x 10 Gbit/s SFP+ ( Intel® )<br>Interface modul for Dynamic LoM 4 x 10 Gbit/s SFP+ ( Intel® )<br>Interface modul for Dynamic LoM 4 x 1 Gbit/s RJ45 ( Intel® )<br>Omni Path 1 x PCIe 3.0 x16 ( Intel® ) |
| <b>Rack infrastructure</b>             | Rackmount kit full extraction (820mm), tool less mounting, length variable 559-914mm<br>Cable Management for 19-inch DataCenter / PRIMECENTER Racks<br>Cable Arm 2U for PRIMECENTER- and 3rd-party racks   |
| <b>Warranty</b>                        |  |
| <b>Warranty period</b>                 | 3 years  |
| <b>Warranty type</b>                   | Onsite warranty  |
| <b>Warranty Terms &amp; Conditions</b> | <a href="http://www.fujitsu.com/support">www.fujitsu.com/support</a>   |

---

**Warranty**

**Product Support Services - the perfect extension**

---

|                             |   |
|-----------------------------|---|
| <b>Support Pack Options</b> | Globally available in major business areas:<br>9x5, Next Business Day Onsite Response Time<br>9x5, 4h Onsite Response Time<br>24x7, 4h Onsite Response Time |
| <b>Recommended Service</b>  | 24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.   |
| <b>Service Lifecycle</b>    | 5 years after end of product life   |
| <b>Service Weblink</b>      | <a href="http://www.fujitsu.com/fts/products/product-support-services/">http://www.fujitsu.com/fts/products/product-support-services/</a>                   |

---

## More information

### Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY RX2540 M4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu PRIMERGY RX2540 M4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/primergy>

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2017 FUJITSU LIMITED

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

**Contact**  
FUJITSU LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2017-08-08 INT-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2017 FUJITSU LIMITED