
Overview

The HP Ethernet 10Gb 2-port 560SFP+ Adapter features the latest Intel 82599 controller. It is a low-cost, low-power dual port PCIe v2.0 x8 adapter designed for HP ProLiant Gen8 and select G7 ML/DL/SL servers. The HP 560SFP+ addresses the demanding needs of the next-generation data center by providing unmatched features for virtualization and scalability that complement the HP Gen8 server platform.

The HP 560SFP+ comes with both low profile and standard brackets and has two SFP+ cages that enable connections with DACs as well as SR fiber optic modules. The HP 560SFP+ adapter supports SR-IOV and high performance networking features such as VLAN tagging, low latency interrupts, TCP and UDP checksum offloading, MSI-X, NIC teaming (bonding), Receive Side Scaling (RSS), jumbo frames, and PXE boot.



Models

HP Ethernet 10Gb 2-port 560SFP+ Adapter

665249-B21

Kit contents

- HP Ethernet 10Gb 2-port 560SFP+ Adapter
- Quick install card
- Product warranty statement



Compatibility

Servers

ProLiant DL (rack-optimized):

- HP ProLiant DL160 Gen8
- HP ProLiant DL165 G7
- HP ProLiant DL320e Gen8
- HP ProLiant DL320e Gen8 v2
- HP ProLiant DL360e Gen8
- HP ProLiant DL360p Gen8
- HP ProLiant DL380e Gen8
- HP ProLiant DL380p Gen8
- HP ProLiant DL385p Gen8
- HP ProLiant DL560 Gen8
- HP ProLiant DL580 G7
- HP ProLiant DL585 G7
- HP ProLiant DL980 G7

ProLiant ML (expansion optimized):

- HP ProLiant ML310e Gen8
- HP ProLiant ML310e Gen8 v2
- HP ProLiant ML350e Gen8
- HP ProLiant ML350p Gen8

ProLiant SL (Scalable Line):

- HP ProLiant SL210t Gen8
- HP ProLiant SL230s Gen8
- HP ProLiant SL250s Gen8
- HP ProLiant SL270s Gen8

NOTE: This is a list of Supported Servers. Some may be discontinued.



Standard Features

Product Features	 Industry-leading throughput and latency performance Up to 40Gb/s bi-directional near line rate throughput Hardware acceleration TCP/IP/UDP stateless intelligent offloads No firmware updates required - less management and downtime Low profile design shipping with standard height and low-profile brackets Supports SR-IOV (requires server FW, SW and OS support) PXE, Jumbo Frames, Checksum & Segmentation Offload, IPv6 and RSS On chip temperature monitor Standard server operating system support Standard NC series option kit warranty, support, services Field replaceable and upgradeable Support for Preboot eXecution Environment (PXE) Integrated PHY and MAC IEEE 1588 (Time Synchronization) The HP 560SFP+ Adapter delivers 20 Gbps full duplex Ethernet transfer rate per port (40 Gbps per adapter), providing the network performance needed to improve response times and alleviate bottlenecks that impact performance of next generation data centers. 10Gb Ethernet bandwidth is ideal for high performance computing, database clusters, video on demand and more.		
Dual-port 10 Gigabit Ethernet Throughput			
PCI Express Interface	The HP 560SFP+ Adapter is designed with an eight lane (x8) PCI Express bus based on the PCIe v2.0 standard. The adapter is backward compatible with four lane (x4) PCI Express, automatically auto-sensing between x8 and x4 slots.		
Jumbo Frames	The HP 560SFP+ Adapter supports jumbo frames (also known as extended frames), permitting up to a 9K byte (KB) transmission unit (MTU) when running Ethernet I/O traffic. This is over 5X the size of a standard 1500-byte Ethernet frame. With jumbo frames, networks can achieve higher throughput performance and greater CPU utilization. These attributes are particularly useful for database transfer and tape backup operations.		
TCP/IP Stateless Offloading	TCP, IP, UDP checksum offload, Large Send Offload (LSO), TCP, Segmentation Offload (TSO). These features optimize host efficiency, leaving the CPU available for other duties. The HP 560SFP+ Adapter powered by Intel® 82599 controller offers TCP/IP stateless intelligent offloading capability.		
MSI and MSI-X	Message Signaled Interrupt (Extended) provides performance benefits for multi-core servers by load balancing interrupts between CPUs/cores. The HP 560SFP+ Adapter supports MSI and MSI-X.		
IEEE 802.1Q virtual local area network (VLAN) protocol allows each physical port of the HP 5 adapter to be separated into multiple virtual NICs for added network segmentation and enha and performance. VLANs increase security by isolating traffic between users. Limiting the br to within the same VLAN domain also improves performance. The HP 560SFP+ Adapter prov for 802.1Q (VLAN).			



Standard Features			
Optimized for Virtualization	I/O Virtualization support for VMware NetQueue, Microsoft VMQ and Virtualization Technology for Connectivity (VT-c) help meet the performance demands of consolidated virtual workloads.		
	Compliant with Single-Root I/O Virtualization (SR-IOV), accommodating multiple Virtual Machines (VMs) to share single PCIe resources. The HP 560SFP+ Adapter supports SR-IOV, requiring software and OS support		
Checksum & Segmentation Offload	Normally the TCP Checksum is computed by the protocol stack. By selecting one of the "Checksum Offload" parameters, the checksum can be computed by the adapter. Segmentation Offload is technique for increasing outbound throughput of high-bandwidth network connections by reducing CPU overhead. The technique is also called TCP segmentation offload (TSO) when applied to TCP, or generic segmentation offload (GSO).		
	The HP 560SFP+ Adapter has Checksum and Segmentation Offload capabilities		
IPv6	IPv6 uses 128-bit addressing allowing for more devices and users on the internet. IPv4 supported 32-bit addressing.		
	The HP 560SFP+ Adapter supports IPv6.		
Receive Side Scaling (RSS)	RSS resolves the single-processor bottleneck by allowing the receive side network load from a network adapter to be shared across multiple processors. RSS enables packet receive-processing to scale with the number of available processors. The HP 560SFP+ Adapter has RSS capabilities.		
Time synchronization implementations (PTP)	Synchronization of system clocks throughout a network, achieving clock accuracy in the sub-microsecond range, making it suitable for measurement and control systems.		
	The HP 560SFP+ Adapter supports Precision Time Protocol-ready (PTP) IEEE 1588 & 802.1AS		
Network Adapter Teaming	The HP 560SFP+ Adapter support for NIC teaming helps IT administrators increase network fault tolerance and increased network bandwidth, The team of adapters can work together as a single virtual adapter. The HP 560SFP+ Adapter provides support for several different types of teaming enabling IT administrators to optimize availability, improve performance and help reduce costs.		



Standard Features

Network Management

Management Support	The HP 560SFP+ Adapter can be administered from HP Systems Insight Manager (SIM). The adapters can be managed individually or in teams, providing SNMP based statistics for reporting purposes. The HP 560SFP+ Adapter can also be managed by other applications with SNMP support.		
Server Integration	The HP 560SFP+ Adapter is a validated, tested, and qualified solution that is optimized for HP ProLiant servers. HP validates a wide variety of major operating systems drivers with the full suite of web-based enterprise management utilities including HP Intelligent Provisioning and HP Systems Insight Manager that simplify network management.		
	This approach provides a more robust and reliable networking solution than offerings from other venders and provides users with a single point of contact for both their servers and their network adapters.		
Configuration Utilities	Each HP 560SFP+ Adapter ships with a suite of operating system-tailored configuration utilities that allow the user to enable initial diagnostics and configure adapter teaming. This includes a patented teaming GUI for Microsoft Windows operating systems. Additionally, support for scripted installations of teams in a Microsoft Windows environment allow for unattended OS installations.		
LED Indicators	The colored LEDs on each port of the HP 560SFP+ Adapter indicate link status and link activity.		
Preboot eXecution Environment (PXE)	PXE allows the server to boot over the network and download software residing in the network.		
HP Sea of Sensors 3D	Support for HP's Sea of Sensors which is a collection of 32 sensors that automatically track thermal activity - heat - across the server. When temperatures get too high, sensors can kick on fans and make other adjustments to reduce energy usage. What makes it better is the upgrade from all six fans kicking on at one time to a new system where only one kicks on - the one in proximity of the area that started heating up - thus reducing the amount of energy used for cooling.		
	VMware NetQueue is technology that significantly improves performance of 10 Gigabit Ethernet network adapters in virtualized environments.		
Queue (VMQ)	Windows Hyper-V VMQ (VMQ) is a feature available on servers running Windows Server 2008 R2 with VMQ- enabled Ethernet adapters. VMQ uses hardware packet filtering to deliver packet data from an external virtual machine network directly to virtual machines, which reduces the overhead of routing packets and copying them from the management operating system to the virtual machine. The HP Ethernet 10Gb 2-port 560SFP+ Adapter support VMware NetQueue and Windows Hyper-V VMQ.		
Warranty	Maximum: The remaining warranty of the HP product in which it is installed (to a maximum three-year, limited warranty). Minimum: One year limited warranty.		
	Additional information regarding worldwide limited warranty and technical support is available at: http://h18004.www1.hp.com/products/servers/platforms/warranty/index.html		



Service and Support

Service and Support

HP Technology Services

HP Technology Services offers you consultants and support experts to solve your most complex infrastructure problems. We help keep your business running, boost availability, and avoid downtime.

Protect your business beyond warranty with HP Care Pack Services

When you buy HP Options, it's also a good time to think about what level of service you may need. HP Care Pack services provide total care and support expertise with committed response choices designed to meet your IT and business need.

HP Foundation Care services deliver scalable support-packages for HP industry-standard servers and software. You can choose the type and level of service that is most suitable for your business needs. New to this portfolio is HP Collaborative Support. If you are running business critical environments, HP offers Proactive Care or Critical Advantage. These services help you deliver high levels of application availability through proactive service management and advanced technical response.

Here is the support service recommendation from the Foundation Care and Proactive Care portfolio. For customized support service solution, HP can work with you to tailor a service solution for your unique support requirements using broader services portfolio of Foundation Care and Proactive Care.

Recommended HP Care Pack Services for optimal satisfaction with your HP product

Recommended Services

3-Year HP 24x7 4 hour Response, Hardware Support Onsite Service

Provides you with rapid remote support and if required an HP authorized representative who will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged.

http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-6547EEE.pdf

OR

3-Year HP 24x7 4 hour Response, HP Collaborative Support

Offers customers a single point of contact for server problem diagnosis, hardware problem resolution, and basic software problem diagnosis, fault isolation, and resolution if available to HP. If the problem is with HP HW, the representative will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged. In case, the issue is with HP or supported third-party software product and cannot be resolved by applying known fixes, HP will contact the third-party vendor and create a problem incident on your behalf.

HP ProLiant Server Hardware Installation

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf



Service and Support

Related HP Care Pack Services to enhance your HP product experience

Related Services	3-Year HP 24x7 4 hour Response, Proactive Care or Critical Advantage Helps optimize your systems and delivers high levels of application availability through proactive service management and advanced technical response. A skilled Technical Manager will own your query or issue end to end until resolved, delivering a single point of contact for you http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-2140ENW.pdf		
	OR		
	3-Year HP 6-hour Onsite Call-to-Repair, HP Collaborative Support Offers customers a single point of contact for server problem diagnosis, hardware problem resolution to return the hardware in operating condition within 6 hours of the initial service request to the HP Global Solution Center, and basic software problem diagnosis, fault isolation, and resolution if available to HP. In case, the issue is with HP or supported third-party software product and cannot be resolved by applying known fixes, HP will contact the third-party vendor and create a problem incident on your behalf.		
	HP Proactive Select Service Provides a flexible way to purchase HP best-in-class consultancy and technical services. You can buy Proactive Select Service Credits when you purchase your hardware and then use the credits over the next 12 months. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3842ENN.pdf		
Insight Remote Support	t Provides 24 X 7 remote monitoring, proactive notifications, and problem resolution. Learn more http://www.hp.com/go/insightremotesupport		
HP Support Center	Personalized online support portal with access to information, tools and experts to support HP business products. Submit support cases online, chat with HP experts, access support resources or collaborate with peers. Learn more http://www.hp.com/go/hpsc		
	HP's Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime. HP Insight Remote Support and HP Support Center are available at no additional cost with a HP warranty, HP Care Pack or HP contractual support agreement.		
	*HP' Support Center Mobile App is subject to local availability		
Parts and materials	HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Supplies and consumable parts will not be provided as part of this service; standard warranty terms and conditions apply. Parts and components that have exceeded their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual or the technical product data sheet will not be provided, repaired or replaced as part of this service.		



Service and Support

Warranty / Service Coverage	For ProLiant servers and storage systems, this service covers HP-branded hardware options qualified for the server, purchased at the same time or afterward, internal to the enclosure, as well as external monitors up to 22" and tower UPS products; these items will be covered at the same service level and for the same coverage period as the server unless the maximum supported lifetime and/or the maximum usage limitation has been exceeded. Coverage of the UPS battery is not included; standard warranty terms and conditions apply.
	The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction. It does not apply to any exchange of Disk or SSD/Flash Drives that have not failed. SSD/Flash Drives that are specified by HP as consumable parts and/or that have exceeded maximum supported lifetime and/or the maximum usage limit as set forth in the manufacturer's operating manual or the technical data sheet are not eligible for the defective media retention service feature option.
For more information	To learn more on services for HP ESSN Options, please contact your HP sales representative or HP Authorized Channel Partner. Or visit: http://www.hp.com/services/proliant or

www.hp.com/services/bladesystem



Related Options

Direct Attach Cable	HP BladeSystem c-Class Small Form-Factor Pluggable .5m 10GbE Copper Cable HP BladeSystem c-Class Small Form-Factor Pluggable 1m 10GbE Copper Cable HP BladeSystem c-Class Small Form-Factor Pluggable 3m 10GbE Copper Cable HP BladeSystem c-Class Small Form-Factor Pluggable 5m 10GbE Copper Cable HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable HP X240 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 1m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable HP X242 SFP+ 15m DAC Cable NOTE: Direct Attach Cable (DAC) must be purchased separately for copper environments.	487649-B21 487652-B21 487655-B21 537963-B21 JD095C JD096C JD097C JG081C JC784C J9281B J9283B J9285B J9287B
Fiber Optic Modules	HP BladeSystem c-Class 10Gb Short Range Small Form-Factor Pluggable Option HP BladeSystem c-Class 10Gb Long Range Small Form-Factor Pluggable Option HP BLc Virtual Connect 1Gb SX Small Form Factor Pluggable Option Kit NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic environments.	455883-B21 455886-B21 453151-B21
Fiber Optic Cables	HP 2M LC-SC Cable Kit (2Gb to 1Gb) 5M LC-SC Cable Kit (2Gb to 1Gb) HP 15M LC-SC Cable Kit (2Gb to 1Gb) HP 2m LC-LC FC Cable Kit 5m LC-LC FC Cable Kit HP 15m LC-LC FC Cable Kit HP 30m LC-LC FC Cable Kit HP 50m LC-LC FC Cable Kit HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic environments. NOTE: For additional information on 10Gb cable specifications go to: http://www.hewlett-packard.com/rnd/pdfs/10gig_cabling_technical_brief.pdf	221691-B21 221691-B22 221691-B23 221692-B21 221692-B22 221692-B23 221692-B26 221692-B27 AJ833A AJ834A AJ836A AJ837A AJ838A AJ839A



Related Options				
Gigabit Server Adapters	HP NC112T PCI Express Gigabit Server Adapter	503746-B21		
	HP NC360T PCI-E Dual Port Gigabit Server Adapter	412648-B21		
	HP NC364T PCI-E Quad Port Gigabit Server Adapter	435508-B21		
	HP NC365T 4-port Ethernet Server Adapter	593722-B21		
	HP NC373F PCI-E Multifunction 1000SX Gigabit Svr Adapter	394793-B21		
	HP NC373T PCI-E Multifunction Gigabit Server Adapter	394791-B21		
	HP NC375T PCI Express Quad Port Gigabit Server Adapter	538696-B21		
	HP NC382T PCI Express Dual Port Multifunction Gigabit Server Adapter	458492-B21		
	HP Ethernet 1Gb 4-port 331T Adapter	647594-B21		
	HP Ethernet 1Gb 2-port 332T Adapter	615732-B21		
	HP Ethernet 1Gb 2-port 361T Adapter	652497-B21		
10 Gigabit Server Adapters	NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter.			
	HP NC522SFP Dual Port 10GbE Gigabit Server Adapter	468332-B21		
	HP NC523SFP 10Gb 2-port Server Adapter	593717-B21		
	HP NC524SFP Dual Port 10GbE Module	489892-B21		
	NOTE: NC524SFP is available only on DL370 G6, ML370 G6, DL580 G7, DL585 G7, and DL980 G7.			
	HP NC550SFP Dual Port 10GbE Server Adapter	581201-B21		
	HP NC552SFP 10Gb 2-port Ethernet Server Adapter	614203-B21		
	HP Ethernet 10Gb 2-port 530SFP Adapter	652503-B21		
	HP Ethernet 10Gb 2-port 530T Adapter	656596-B21		
	HP Ethernet 10Gb 2-port 560SFP+ Adapter	665249-B21		
	HP Ethernet 10Gb 2-port 561T Adapter	716591-B21		
	HP Ethernet 10Gb 2-port 570SFP+ Adapter	718904-B21		
FlexibleLOM Adapters	NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter.			
	Ethernet Adapters			
	HP Ethernet 1Gb 4-port 331FLR Adapter	629135-B21		
	HP Ethernet 1Gb 4-port 366FLR Adapter	665240-B21		
	HP Ethernet 10Gb 2-port 530FLR-SFP+ Adapter	647581-B21		
	HP Ethernet 10Gb 2-port 560FLR-SFP+ Adapter	665243-B21		
	HP Ethernet 10Gb 2-port 561FLR-T Adapter	700699-B21		
	HP Ethernet 10Gb 2-port 570FLR-SFP+ Adapter	717491-B21		
	FlexFabric Adapters			
	HP FlexFabric 10Gb 2-port 526FLR SFP+ Adapter	629138-B21		
	HP FlexFabric 10Gb 2-port 533FLR-T Adapter	700759-B21		
	HP FlexFabric 10Gb 2-port 534FLR-SFP+ Adapter	700751-B21		
	HP FlexFabric 10Gb 2-port 554FLR-SFP+ Adapter	629142-B21		
	NOTE: Please see the QuickSpecs for Technical Specifications and additional			
	information: www.hp.com/go/ProLiantNICs			



Technical Specifications

General Specifications	Network Processor	Intel [®] 82599 Controller	
	Data rate	Two ports, each at 20 Gbp theoretical bandwidth.	s full duplex; 40 Gbps aggregate full duplex
	Onboard Memory	256MB	
	Bus type	PCI-e v2.0 at 8 GT/s, x8	
	Form factor	Standard and low profile a	dapter compliant with the PCIe standard
	IEEE Compliance	802.3, 802.1ab, 802.3x, 802.3ad, 802.3p, 802.1q, 802.3ae, 802.1au, 802.3ap 802.1as, 802.3ak,802.1qaz, 802.1Qbb	
Power and Environmental	Operating	Temperature	32° to 131° F (0° to 55° C)
Specifications		Humidity	5% to 95% non-condensing
	Power	10.8W maximum (10 W Ty	pical)
	Emissions classification	Class B	
	Agency Approvals	USA	FCC Part 15 Class B
		Canada	ICES=3, Issue 5
		Japan	VCCI 2011-04 Class B
		International	EN55022:2010 + Class B, EN55024:2010; EN61000-3-2:2006, EN61000-3-3:2008
		Taiwan	BSMI, CNS13438 (2006) Class B
		Australia/New Zealand (AS/NZS):	AS/NZS CISPR 22: 2009+A1:2010 Class
		Korea	KN22 Class B, KN24
	RoHS Compliance	5 of 6	
	Safety	UL Mark (USA and Canada)	
		CE Mark	
		EN 605901 2nd edition	
Operating System Support	Microsoft Windows Server 2008, Server 2008R2, and HPC Server 2008, 32 and 64-bit Microsoft Windows Server Hyper-V Microsoft Windows Small Business Server 2011 Red Hat Enterprise Linux 5.7 and 6.1 SLES 10 and 11 VMware 4.1u2 and 5.0u1 Solaris 10 NOTE: For more Linux OS support & certification information, please visit our the ProLiant & BladeSystem Server Linux matrix: http://h18004.www1.hp.com/products/servers/linux/hplinuxcert.html		



Technical Specifications

Environment-friendly End-of-life Management Products and Approach and Recycling	Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: http://www.hp.com/go/green. To recycle your product, please go to: http://www.hp.com/go/green or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.	
		The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/green. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

© Copyright 2013 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Windows is a US registered trademark of Microsoft Corporation.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

