


HT 221 PPB

54,6 cm / 21.5" Diagonal
LED Backlight – Format 16:9

- 21,5" Touch Monitor LED Backlight
- 1920 x1080 Full HD Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- Triple Input: DP + HDMI + VGA
- Built-In Stereo Speakers
- IP65 Rating Level
- Display Protection: Thickness 3mm
- Multi-Video Modes
- Wall-Mountable (VESA)
- Edge to Edge Glass without raised frame



54,6 cm / 21.5"

The monitor stand is not included. A VESA compatible stand can be purchased separately for desktop usage.

Part. No.: HT 221 PPB

SIZE, RESOLUTION



21.5"
16:9 Aspect Ratio



Full HD
1920 x 1080

CONNECTIVITY, SPEAKER



VGA
HDMI
DP



Built-In
Stereo Speaker

VIEWING ANGLE, VESA



178° Wide
Viewing Angle




VESA
Wall-Mountable

OTHER FEATURES



10
Point
Touch



Panel
Brightness





IP65



≥ 6H
Hardness

Display Size	54,6cm / 21.5" Diagonal
Panel Type	TFT – LED Backlight, VA Panel *
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	350 cd/m ² (Panel) – 300 cd/m ² (Monitor)
Contrast (Typ.)	1.000:1 (Typical)
Contrast (Active)	5.000.000:1 (Active)
Viewing Angle L/R; U/D	178° H – 178° V (CR >10)
Response Time	4 msec
Pixel Pitch	0,248 (H) x 0,248 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch Cover Glass + LOCA + ITO Glass
Display Colors	16.7M Colors
Horizontal Frequency	30 ~ 83 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	D-Sub (VGA)
Input 2	HDMI
Input 3	Display Port
Input 4	USB 3.0 x 1 (for touch)
Buil-in Speakers	Yes, 2W x 2; Earphone Jack
Power Consumption	On: 13W; Stand-by: 0,37W; Off: 0,2W
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 65 Hz
Product Dimensions	510,9 x 49,1 x 313 mm (W x D x H)
Packing Dimensions	563 x 101 x 428 mm (W x D x H)
Net / Gross Weight	4,14 Kg / 5,34 Kg (± 0,3Kg)
Bezel & Color Plan	Front TP: Black Color; Bezel, Back Cover: Black Color



VESA Mounting	100 x 100 mm
Monitor Stand	Not included. A VESA compatible stand can be purchased separately for desktop usage.
Tilt / Kensington Lock	- / Yes
Display Protection	Thickness 3 mm
Hardness / Transmittance	≥6H Toughened hard panel surface / ≥85%
IP Rating Level	IP 65 ** (Front), Water and Dust Protection
Controls	Menü, (+), (-), AUTO, Power
Color	9300, 6500, 5500, User Mode
Preset Mode	PC, Movie, Game, ECO Modes
On Screen Display	11 OSD Languages
Accessory	Power Cable (1,5m); HDMI Cable (1.5m); USB 2.0 (B-A) Cable (1.8m); Warranty Card; Quick Start Guide

Supplier's Name	HT221PPB
Model Name	D
Energy efficiency class for standard Dynamic Range (SDR)	13 kWh/1000h
Annual Energy Power Consumption (kWh/1000h)	13 W
On mode power demand for Standard Dynamic Range (SDR)	0,2 W
Off mode power demand (W)	0,4 W
Standby mode power demand (W)	54,6cm / 21,5"
Screen Diagonal (cm / inches)	1920 x 1080
Resolution	HT221PPB

PART. NO.:
HT 221 PPB

4 711404 023347 >

© 2021 HANNspree Europe Holdings B.V. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies.

* IP65: The IP Code classifies how resistant a device is to foreign objects and moisture. IP65 means that the monitor is protected from total dust ingress and it is protected against low pressure water jets from any direction. Limited ingress permitted.

** "VA" word mark / trademark and related patents on technologies belong to their respective owners.