

MPN: V-UTP6A0025S-SLIM

CAT6a U/UTP SLIM Network Cable

0.25m, Black

CAT6a slim cables is an updated version of CAT6 slim cables. These are perfect for installations where you need to save space in IT Racks and Cabinets. They cables are thinner and very flexible which provides the installer a better accessibility and quick and easy switching. Furthermore it improves the Air-Flow, and thereby reducing the risk of down-time. All the cables are tested tested up to 500Mhz / 1000 Mbps (CAT6a standard) and are backwards compatible with CAT6, CAT5e and CAT5 cables. Each cable are manufactured with a snagless with prevents the connector do be damaged when you install the cable through an installation with very less space.

- LSZH (Low Smoke Zero Halogen)
- CAT6a tested up to 500 MHz
- with snagless
- with gold-plated pins
- low cable diameter: 3,6mm
- very flexible, very easy to move to save space behind baseboards
- Support PoE++



Specifications

Features	AWG wire size	28	
	Cable length	0.25 m	
	Cable shielding	U/UTP (UTP)	
	Cable standard	Cat6a	
	Conductor material	Copper	
	Conductor type	Stranded	
	Connector 1	RJ45	
	Connector 1 gender	Male	
	Connector 2	RJ45	
	Connector 2 gender	Male	
	Data transfer rate	10000 Mbit/s	
	Frequency	500 MHz	
	Halogen-free	Yes	
	Jacket material	Low smoke zero halogen (LSZH)	
	Product colour	Black	
	RoHS compliance	Yes	
	Snagless cable boot	Yes	
	Other features	Product series	Slim Cable
		Technical features	Boot with kink protection, strain relief and latch protection
Package dimensions (verified)	Depth Verified	12.1 cm	
	Gross Weight Verified	0.012 kg	
	Height Verified	1.5 cm	

Package dimensions	Width Verified	15.8 cm
Packaging data	Quantity per pack	1 pc(s)
Product dimensions	Net Weight (Product, kg)	0.002 kg
Technical details	Doesn't contain	Halogen
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Outer diameter	3.6 mm

Other products in this series

Cable length	Black	Blue	Green	Grey
0.15	V-UTP6A0015S-SLIM	V-UTP6A0015B-SLIM		V-UTP6A0015-SLIM
0.2		V-UTP6A002B-SLIM		
0.25	V-UTP6A0025S-SLIM	V-UTP6A0025B-SLIM	V-UTP6A0025G-SLIM	V-UTP6A0025-SLIM
0.3		V-UTP6A003B-SLIM		
0.5	V-UTP6A005S-SLIM	V-UTP6A005B-SLIM	V-UTP6A005G-SLIM	V-UTP6A005-SLIM
1.0	V-UTP6A01S-SLIM	V-UTP6A01B-SLIM	V-UTP6A01G-SLIM	V-UTP6A01-SLIM
1.5	V-UTP6A015S-SLIM	V-UTP6A015B-SLIM	V-UTP6A015G-SLIM	V-UTP6A015-SLIM
2.0	V-UTP6A02S-SLIM	V-UTP6A02B-SLIM	V-UTP6A02G-SLIM	V-UTP6A02-SLIM
3.0	V-UTP6A03S-SLIM	V-UTP6A03B-SLIM	V-UTP6A03G-SLIM	V-UTP6A03-SLIM
4.0		V-UTP6A04B-SLIM		
5.0	V-UTP6A05S-SLIM	V-UTP6A05B-SLIM	V-UTP6A05G-SLIM	V-UTP6A05-SLIM
7.5	V-UTP6A075S-SLIM	V-UTP6A075B-SLIM	V-UTP6A075G-SLIM	V-UTP6A075-SLIM
10.0	V-UTP6A10S-SLIM	V-UTP6A10B-SLIM	V-UTP6A10G-SLIM	V-UTP6A10-SLIM
15.0		V-UTP6A15B-SLIM		
20.0		V-UTP6A20B-SLIM		

Cable length	Red	White	Yellow
0.15		V-UTP6A0015W-SLIM	
0.2			
0.25	V-UTP6A0025R-SLIM	V-UTP6A0025W-SLIM	V-UTP6A0025Y-SLIM
0.3			
0.5	V-UTP6A005R-SLIM	V-UTP6A005W-SLIM	V-UTP6A005Y-SLIM
1.0	V-UTP6A01R-SLIM	V-UTP6A01W-SLIM	V-UTP6A01Y-SLIM
1.5	V-UTP6A015R-SLIM	V-UTP6A015W-SLIM	V-UTP6A015Y-SLIM
2.0	V-UTP6A02R-SLIM	V-UTP6A02W-SLIM	V-UTP6A02Y-SLIM
3.0	V-UTP6A03R-SLIM	V-UTP6A03W-SLIM	V-UTP6A03Y-SLIM
4.0			
5.0	V-UTP6A05R-SLIM	V-UTP6A05W-SLIM	V-UTP6A05Y-SLIM
7.5	V-UTP6A075R-SLIM	V-UTP6A075W-SLIM	V-UTP6A075Y-SLIM
10.0	V-UTP6A10R-SLIM	V-UTP6A10W-SLIM	V-UTP6A10Y-SLIM
15.0			
20.0			

Other images

