

PCIe JL82599EN Single-SFP+ Fiber 10G Server NIC



USER Manual
EN ver2.0

Description

PCI Express 8X Network adapter adopts Intel third-generation WMB network controller 82599EN ,By providing unparalleled features of virtualization, flexible features of LAN and SAN network, and proven reliable performance, it solves the high requirements of the generation data center, it has Single 10Gps SFP+ port which can setup a long-distance link with a file server or a remote workstation.

Specification

- PCI-Express host interface specification v2.0 with 5GT/s BUS width
- PCI-Express lanes: x8
- Complies with single port 10GbE SFP port
- Complies with IEEE802.3ae specification
- Layer 2 functions: IEEE 802.3x Flow Control - IEEE 802.1q VLAN
- Supports Receive-side scaling (RSS)
- Supports IPv 4, IPv 6 protocols
- Supports Jumbo Frames up to 15.5K
- Supports Checksum offloading
- Statistics for management and RMON
- Support for virtual machines device queues
- Interrupt throttling control to limit maximum interrupt rate and improve CPU usage
- Chipset: Intel JL82599EN
- Drivers support for FreeBSD*8.0, EFI*1.1, UEFI*2.1, Win7/ Win-server2008 R2/Win-server2008 R2 Core/ Linux SLES 11 SP1/ Win Vista*SP2/Win-server2003 SP2/Win-server2007 SP2/ Win-server2008 SP2 Core/Win-server2012/ Win8/Win8.1/Win-server2016/win10, Linux* Stable Kernel version2.6/Linux RHEL 4.8/ Linux RHEL 5.5/ Linux SLES 10 SP3/ Linux SLES 11

Package content

- 1 x SFP+ PCIe Network card
- 1 x User's Manual
- 1 x CD Driver
- 1 x Low profile bracket
- **Accessories**



System Requirements

- FreeBSD*8.0, EFI*1.1, UEFI*2.1, Win7/ Win-server2008 R2/Win-server2008 R2 Core/ Linux SLES 11 SP1/ Win Vista*SP2/Win-server2003 SP2/Win-server2007 SP2/ Win-server2008 SP2 Core/Win-server2012/ Win8/Win8.1/Win-server2016/win10, Linux* Stable Kernel version2.6/Linux RHEL 4.8/ Linux RHEL 5.5/ Linux SLES 10 SP3/ Linux SLES 11
- Available PCI Express x8/x16 slot

Cabling Requirements:

Intel 10Gigabit adapters

- SFP+ Module Laser wavelength:850 nanometer (not visible)
- **LC Cable type:**
 - Multi-mode fiber with 50 micron core diameter, maximum length is 550 meters
 - Multi-mode fiber with 62.5 micron core diameter, maximum length is 275 meters
 - Connector type: LC
- SFP+ Module laser wavelength:1310 nanometer(not visible)
- **LC Cable type:**
 - Multi-mode fiber with 9 micron core diameter, maximum length is 3K meters
- **10 Gigabit Ethernet over SFP+ Direct Attached cable(Twinaxial)**
 - Length 10 meters max.

Hardware installation

1. Turn off the computer and unplug the power cord

2. Remove the computer cover and the adapter slot cover from the slot that matches your adapter
3. Insert the adapter edge connector into the slot and secure the bracket to the chassis
4. Replace the computer cover ,then plug in the power cord
5. Power on the computer

Note: select the correct slot, some systems have physical X8 PCI Express slots that actually only support lower speeds. Please check your system manual to identify the slot

Install Drivers and software

Windows[®] Operating Systems

You must have administrative rights to the operating system to install the drivers.

1. insert the CD driver bound with Intel network driver into your CD-ROM drive(also you can download the latest drivers from):
2. if the Found New Hardware Wizard screen is displayed, click **Cancel**
3. start the autorun located in the software package, the autorun may automatically start after you have extracted files.
4. Click **install Drivers and Software**
5. Follow the instructions in the install wizard to finish it

Installing Linux Drivers from Source Code

1. Download and expand the base driver tar file.
2. Compile the driver module
3. Install the module using the modprobe command
4. Assign an IP address using the ifconfig command

Support

More information and settings, please refer to the Intel Adapter User Guides or you can contact us.