



19-inch diagonal widescreen LCD monitor with an IWC Stand for simple PC and monitor configurations

HP L1908wi Flat Panel Monitor

The HP L1908wi 19-inch Widescreen LCD Monitor offers a unique, modular approach that combines the superior front of screen performance of a wideformat large-screen LCD monitor with the convenience of a stand designed to house an HP Compaq dc7800 Ultra-slim Desktop PC or HP Thin Client for a compact configuration that makes more efficient use of space-constrained environments.

Improved technology

This monitor features many of the latest flat panel technologies available, including: widescreen 1440 x 900 resolution; substantial brightness (up to 300 cd/m2) ¹; high contrast ratio (up to 800:1) ¹; improved response times (as fast as 5 ms) ¹; wide viewing angles that enable comfortable viewing from anywhere in the room; a full range of tilt, swivel, and height-adjustment settings to help you find a comfortable viewing position

Smart software

HP Display LiteSaver allows Sleep mode scheduling at preset times to help protect against image retention and lower power consumption and energy costs. HP Display Assistant enables monitor adjustment and color calibration through the connected PC.

Exclusive design

The HP L1908wi monitor includes the HP Quick Release and the HP Compaq dc7800 Series Integrated Work Center (IWC) Stand designed for the full-featured HP Compaq dc7800 USDT PC and HP Thin Clients (sold separately). The monitor helps simplify placement of PC/thin client and monitor solutions in space-constrained and public-traffic areas, including: retail POS/kiosks; mainstream office/cubicles; financial/trading environments; healthcare/laboratories. The built-in IWC Stand stores the PC or thin client securely and out of the way behind the monitor. The convenient cable management solution keeps all of the PC cables together and hidden from view.

Service and support

The HP L1908wi monitor comes with a three-year limited warranty, which makes them easy for IT departments to purchase, install, and maintain. The HP warranty is supported by 65,000 IT service and support professionals in 160 countries around the world.



HP L1908wi Flat Panel Monitor

| Туре | Active Matrix TFT (thin film transistor); Anti-glare and anti-static coatings |
|-----------------------------------|--|
| Picture tube | 19 inches widescreen |
| Viewable image area | 19 inches diagonal |
| Viewing angle | 160° horizontal, 160° vertical |
| Brightness | 300 nits |
| Contrast ratio | 1000:1 |
| Response rate | 5 ms |
| Dot/Pixel pitch | 0.285 mm |
| Frequency | Horizontal frequency: 24-83 kHz, Vertical frequency: 50-76 Hz |
| Resolution | 1440 x 900 @ 60 Hz (native), all VESA modes up to 1280 x 1024 @ 75 Hz |
| Input signal | 15-pin D-sub VGA |
| Video cable | VGA |
| User controls (on-screen display) | Brightness, contrast, positioning, color temperature (6500k, 9300k, custom), individual color control, serial number, display, clock, clock phase, monitor management, factory reset, zoom |
| Base features | Tilt range: -3° to + 20° vertical tilt, swivel range: -180° to +180°, height adjust: 135 mm, detachable base. |
| Software | HP Display Assistant is a software utility that enables theft deterrence and allows monitor adjustment and color calibration using the Display Data Channel Command Interface (DDC/CI) protocol of the connected PC HP Display LiteSaver feature allows you to schedule Sleep mode at preset times to help protect the monitor against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor |
| Power consumption | 50 watts maximum, 37 watts typical |
| Power supply | Auto-sensing, 100 to 240 VAC, Internal power supply, 50 to 60 Hz (built-in power supply) |
| Power Consumption, Standby | 2 watts |
| Dimensions (W x D x H) | 44.6 x 5.9 x 30.1 cm |
| Weight | 7.5 kg |
| Certifications, compliances | TCO'03, ISO 13406-2 VDT Guidelines Approval, CISPR Requirements, VCCI Approvals, MIC (Korean) Requirements, CSA, Australian ACA Approval, "GS" Mark, TUV Approvals, CE Marking, FCC Approval, ENERGY STAR® Qualified, PC-2001 Certified, Microsoft® Windows® Certification (Microsoft® Windows® 98, Microsoft Windows 2000, Microsoft Windows XP, and Windows Vista®) |
| Warranty | Limited 3 years parts, labour and on-site service, including backlight. Availability varies by region. Certain restrictions and exclusions apply. For details, contact HP Customer Support or Service |

¹ All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

© 2008 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the U.S. or other countries. Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries.



HP L1908wi Flat Panel Monitor

Recommended accessories

HP Flat Panel Speaker Bar

Attach seamlessly to the front bezel of your monitor to add full multimedia support features, including stereo speakers with full sound range and an external jack for headphones.



Product number: EE418AA

HP Kensington Security Lock

Peace of mind in an instant. This handy cable lock device attaches itself to your hardware and is then secured to an anchor point in your workspace, ensuring your hardware remains exactly where it should



Product number: PC766A

