

MPN: MC-HDM191910V2.1 HDMI Cable 8K, 10m

Ultra High-Speed 8K@60Hz 48Gbit HDMI 2.1 Cable with Dynamic HDR and enhanced Audio Return Channel (eARC). Supports resolutions up to 10K and refresh rates up to 120Hz. This cable is backwards compatible

- HDMI 2.1 8K60Hz
- 48Gbps
- Support YUV sampling: 4:4:4
- HDCP 2.2
- Great Performance



Specifications

Features

3D	Yes
Audio Return Channel (ARC)	Yes
AWG wire size	28
Bandwidth	120 MHz
Cable jacket material	Polyvinyl chloride (PVC)
Cable length	10 m
Cable material	Copper
Colour sampling	4:4:4
Connector 1	HDMI Type A (Standard)
Connector 1 form factor	Straight
Connector 1 gender	Male
Connector 2	HDMI Type A (Standard)
Connector 2 form factor	Straight
Connector 2 gender	Male
Connector contacts plating	Gold
Data transfer rate	48 Gbit/s
Dolby technologies	DTS-HD Master Audio, Dolby TrueHD
HDCP	Yes
HDCP version	1.4/2.2
HDMI Ethernet channel	Yes
HDMI version	2.1
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
High Dynamic Range 10 (HDR10)	Yes
Maximum refresh rate	120 Hz
Maximum resolution	7680 x 4320 Pixels
Plug and Play	Yes



Features	Product colour	Black
	Quantity per pack	1 pc(s)
	RGB support	4:4:4
	RoHS compliance	Yes
	Supported graphics resolutions	7680 x 4320
	Supported video modes	2160p, 4320p
Operational conditions	Operating temperature (T-T)	-20 - 60 °C
Other features	Quantity	1
Package dimensions	Depth (package,cm)	17.7 cm
	Gross Weight (Package, kg)	0.32 kg
	Height (package,cm)	5.3 cm
	Width (package,cm)	20.6 cm
Product dimensions	Net Weight (Product, kg)	0.25 kg
Technical details	Sustainability certificates	CE, REACH, RoHS
	Sustainability compliance	Yes
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Cable diameter	7.3 mm



Other products in this series

Cable length	
0.5	MC-HDM19190.5V2.1
1.0	MC-HDM19191V2.1
1.5	MC-HDM19191.5V2.1
2.0	MC-HDM19192V2.1
3.0	MC-HDM19193V2.1
4.0	MC-HDM19194V2.1
5.0	MC-HDM19195V2.1
7.5	MC-HDM19197.5V2.1
10.0	MC-HDM191910V2.1



Other images

