

MPN: PE160418A

Power Cord Swiss (Type J) - C13 Angled, 1.8m

This Power cord (Type J) enables you to connect a monitor, PC or a projector to a power source.

• Can only be used in Liechtenstein, Rwanda, Switzerland



Specifications

| Cable type | Features | Cable length | 1.8 m |
|--|--------------------|--------------------------|--------------------------|
| Connector 1 Connector 1 form factor Straight Connector 1 gender Male Connector 2 Connector 2 Connector 2 Connector 2 Connector 2 form factor Angled Connector 2 gender Connector 2 gender Core size O.75 mm² Jacket material Polyvinyl chloride (PVC) Number of cable cores Product colour RoHS compliance Ves Package dimensions (verified) Cross Weight Verified Dipt verified Dipt current Number of Connector 2 gender Depth Verified Dipt current Dipt current Dipt current Dipt current Dipt current Dipt voltage Maximum current Dipt Verified | | Cable type | H05VV-F3G |
| Connector 1 form factorStraightConnector 1 genderMaleConnector 2C13 couplerConnector 2 form factorAngledConnector 2 genderFemaleCornector 2 genderFemaleCore size0.75 mm²Jacket materialPolyvinyl chloride (PVC)Number of cable cores3Product colourBlackRoHS complianceYesPackage dimensions (verified)15.8 cm(Verified)0.172 kgHeight Verified5.5 cmWidth Verified27.4 cmPowerInput current16 AInput voltage250 VMaximum current10 AProduct dimensionsNet Weight (Product, kg)0.17 kgVendor informationBrand NameMicroConnect | | Conductor material | Copper |
| Connector 1 genderMaleConnector 2C13 couplerConnector 2 form factorAngledConnector 2 genderFemaleCore size0.75 mm²Jacket materialPolyvinyl chloride (PVC)Number of cable cores3Product colourBlackRoHS complianceYesPackage dimensions (verified)0.172 kgHeight Verified5.5 cmWidth Verified27.4 cmPowerInput current16 AInput voltage250 VMaximum current10 AProduct dimensionsNet Weight (Product, kg)0.17 kgVendor informationBrand NameMicroConnect | | Connector 1 | Swiss Power Type J |
| Connector 2 C13 coupler Connector 2 form factor Angled Connector 2 gender Female Core size 0.75 mm² Jacket material Polyvinyl chloride (PVC) Number of cable cores 3 Product colour Black RoHS compliance Yes Package dimensions (verified) 15.8 cm (verified) Gross Weight Verified 0.172 kg Height Verified 5.5 cm Width Verified 27.4 cm Power Input current 16 A Input voltage 250 V Maximum current 10 A Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | Connector 1 form factor | Straight |
| Connector 2 form factorAngledConnector 2 genderFemaleCore size0.75 mm²Jacket materialPolyvinyl chloride (PVC)Number of cable cores3Product colourBlackRoHS complianceYesPackage dimensions (verified)Depth Verified15.8 cm(Verified)Gross Weight Verified0.172 kgHeight Verified5.5 cmWidth Verified27.4 cmPowerInput current16 AInput voltage250 VMaximum current10 AProduct dimensionsNet Weight (Product, kg)0.17 kgVendor informationBrand NameMicroConnect | | Connector 1 gender | Male |
| Connector 2 gender Female Core size 0.75 mm² Jacket material Polyvinyl chloride (PVC) Number of cable cores 3 Product colour Black RoHS compliance Yes Package dimensions (verified) Cross Weight Verified 0.172 kg Height Verified 5.5 cm Width Verified 27.4 cm Power Input current 16 A Input voltage 250 V Maximum current 10 A Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | Connector 2 | C13 coupler |
| Core size 0.75 mm² Jacket material Polyvinyl chloride (PVC) Number of cable cores 3 Product colour Black RoHS compliance Yes Package dimensions (verified) 15.8 cm (verified) Gross Weight Verified 0.172 kg Height Verified 5.5 cm Width Verified 27.4 cm Power Input current 16 A Input voltage 250 V Maximum current 10 A Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | Connector 2 form factor | Angled |
| Package dimensions (verified)Depth Verified Gross15.8 cmPowerHeight Verified Maximum current27.4 cmPower dimensions (verified)Input current Input voltage Maximum current16 APower dimensions (verified)250 VPower dimensions (verified)27.4 kgPower dimensions (verified)27.4 cmPower dimensions (verified)27.4 cmProduct dimensions (verified)250 VMaximum current (verified)10 AProduct dimensions (verified)Net Weight (Product, kg)0.17 kgVendor information (verified)Brand Name (verified)MicroConnect | | Connector 2 gender | Female |
| Number of cable cores3Product colourBlackRoHS complianceYesPackage dimensions (verified)Depth Verified15.8 cmGross Weight Verified0.172 kgHeight Verified5.5 cmWidth Verified27.4 cmPowerInput current16 AInput voltage250 VMaximum current10 AProduct dimensionsNet Weight (Product, kg)0.17 kgVendor informationBrand NameMicroConnect | | Core size | 0.75 mm ² |
| Product colour RoHS compliance Package dimensions (verified) Package dimensions (verified) Poss Weight Verified Depth Verified | | Jacket material | Polyvinyl chloride (PVC) |
| Package dimensions (verified)Depth Verified15.8 cmCross Weight Verified0.172 kgHeight Verified5.5 cmWidth Verified27.4 cmPowerInput current16 AInput voltage250 VMaximum current10 AProduct dimensionsNet Weight (Product, kg)0.17 kgVendor informationBrand NameMicroConnect | | Number of cable cores | 3 |
| Package dimensions (verified) Depth Verified Oross Weight Verified Depth Verified Oross Weight Verified Depth Verified Oross Weight Verified Depth Veri | | Product colour | Black |
| (verified) Gross Weight Verified 0.172 kg Height Verified 5.5 cm Width Verified 27.4 cm Power Input current 16 A Input voltage 250 V Maximum current 10 A Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | RoHS compliance | Yes |
| Height Verified Width Verified Power Input current Input voltage Aximum current In A Product dimensions Net Weight (Product, kg) Vendor information Input verified Unit voltage Uni | | Depth Verified | 15.8 cm |
| Power Input current 16 A Input voltage 250 V Maximum current 10 A Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | Gross Weight Verified | 0.172 kg |
| Power Input current 16 A Input voltage 250 V Maximum current 10 A Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | Height Verified | 5.5 cm |
| Input voltage 250 V Maximum current 10 A Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | Width Verified | 27.4 cm |
| Maximum current 10 A Product dimensions Net Weight (Product, kg) Vendor information Brand Name MicroConnect | Power | Input current | 16 A |
| Product dimensions Net Weight (Product, kg) 0.17 kg Vendor information Brand Name MicroConnect | | Input voltage | 250 V |
| Vendor information Brand Name MicroConnect | | Maximum current | 10 A |
| | Product dimensions | Net Weight (Product, kg) | 0.17 kg |
| Mayantra 27 Voor(a) | Vendor information | Brand Name | MicroConnect |
| vvarranty 25 Year(s) | | Warranty | 25 Year(s) |



Other products in this series

| Cable length | |
|--------------|-------------|
| 1.8 | PE160418 |
| 3.0 | PE160430 |
| 5.0 | PE160450-AG |