

MPN: FIB420001

Optical Fibre Cable, LC-SC, Multimode, Duplex, OM1 (Orange), 1m

The 62.5/125µm OM1 multimode fiber optic cable is suitable for fast Ethernet, gigabit Ethernet and fiber channel applications, such as in data centers, telecom rooms, server farms, cloud storage networks and any place where fiber jumper cables are needed. OM1 patch cords are manufactured using LSZH cables which conform to IEC, EIA TIA or Telcordia standards.

- Designed for Data Centers, Industry and Computer Centers
- LSZH (Low Smoke Zero Halogen) and flame retardant
- RoHS compliant



Specifications

Features	Cable length	1 m
	Cladding diameter	125 µm
	Connector 1	LC/UPC
	Connector 1 gender	Male
	Connector 2	SC/UPC
	Connector 2 gender	Male
	Core diameter	62.5 µm
	Fiber mode structure	Multi-mode
	Fibre optic type	OM1
	Full duplex	Yes
	Halogen-free	Yes
	Insertion loss	0.3 dB
	Jacket material	Low smoke zero halogen (LSZH)
	Product colour	Orange
	RoHS compliance	Yes
Operational conditions	Operating temperature (T-T)	-40 - 85 °C
	Storage temperature (T-T)	-40 - 85 °C
Package dimensions (verified)	Depth Verified	15.3 cm
	Gross Weight Verified	0.038 kg
	Height Verified	1.3 cm
	Width Verified	16 cm
Product dimensions	Net Weight (Product, kg)	0.01 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Cable diameter	2 mm

Other products in this series

Cable length	OM1	OM2	OM3	OM4
0.5	FIB4200005	FIB4220005-2	FIB4220005	FIB4220005P
1.0	FIB420001	FIB422001-2	FIB422001	FIB422001P
1.5			FIB4220015	FIB4220015P
2.0	FIB420002	FIB422002-2	FIB422002	FIB422002P
3.0	FIB420003	FIB422003-2	FIB422003	FIB422003P
5.0	FIB420005	FIB422005-2	FIB422005	FIB422005P
6.0			FIB422006	
7.0	FIB420007	FIB422007-2	FIB422007	FIB422007P
9.0			FIB422009	
10.0	FIB420010	FIB422010-2	FIB422010	FIB422010P
12.0				FIB422012P
15.0	FIB420015	FIB422015-2	FIB422015	FIB422015P
20.0	FIB420020	FIB422020-2	FIB422020	FIB422020P
25.0	FIB420025	FIB422025-2	FIB422025	FIB422025P
30.0			FIB422030	FIB422030P
35.0			FIB422035	
40.0			FIB422040	
50.0			FIB422050	

Cable length	OM5
0.5	FIB5610005
1.0	FIB561001
1.5	
2.0	FIB561002
3.0	FIB561003
5.0	FIB561005
6.0	
7.0	FIB561007
9.0	
10.0	FIB561010
12.0	
15.0	FIB561015
20.0	FIB561020
25.0	FIB561025
30.0	

Cable length	OM5
35.0	
40.0	
50.0	

Other images

