

MPN: FIB996015

Optical Fibre Cable, MPO Female - MPO Female, Multimode, 12 Fibers, Polarity B, Polishing : UPC, OM3 (Aqua Blue), 5m

The 50/125µm OM3 multimode bend insensitive fiber optic cable is less attenuation when bent or twisted compared with traditional optical fiber cables and this will make the installation and maintenance of the fiber optic cables more efficient. This 50/125 OM3 multimode fiber optic cable is ideal for connecting 10G SR, 10G LRM, SFP+ transceivers etc. for 10G/40G/100G Ethernet connections and is the preferred fiber specification for 10G Ethernet connections. The multimode patch cords are manufactured using LSZH cables which conform to IEC, EIA TIA or Telcordia standards.



- Designed for Data Centers, Industry and Computer Centers
- LSZH (Low Smoke Zero Halogen) and flame retardant
- RoHS compliant
- Reduces the amount of insertion loss
- ability to route dozens of individual fiber strands

Specifications

Features	Cable length	15 m
	Cable type	LSZH
	Cladding diameter	125 µm
	Connector 1	MPO/UPC
	Connector 1 gender	Female
	Connector 2	MPO/UPC
	Connector 2 gender	Female
	Core diameter	50 µm
	Fiber mode structure	Multi-mode
	Fibre optic type	OM3
	Halogen-free	Yes
	Insertion loss	0.3 dB
	Jacket material	Low smoke zero halogen (LSZH)
	Product colour	Aqua colour
RoHS compliance	Yes	
Operational conditions	Operating temperature (T-T)	-40 - 85 °C
	Storage temperature (T-T)	-40 - 85 °C
Package dimensions	Gross Weight (Package, kg)	0.5 kg
Packaging data	Quantity	1
	Quantity per pack	1 pc(s)
Product dimensions	Net Weight (Product, kg)	0.4 kg

Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Cable diameter	3 mm