


NOTES:

- ELECRICAL:**
- (1). 100% CONTINUITY (OPEN, SHORT, MISSWIRE) ;
 - (2). INSULATION RESISTANCE: 300V, 5MΩ MIN;
 - (3). CONDUCTIVE RESISTANCE: :5Ω MAX;
 - (4). 100% COMPUTER TEST: 4K*2K@60HZ;
 - (5). WIRE SURFACE PRINTING (White): /

⑧	PE BAG	PE BAG: W155*L175*T0.05mm	1	PCS
⑦	MINI TIE	TIE, METAL MATERIAL INSIDE, BLACK OUTSIDE	1	PCS
⑥	O-ring	O-ring GREEN COLOR	2	PCS
⑤	OUTER MOLD	87A TPU, COLOR FOR BLACK	2	PCS
④	INNER MOLD	LDPE, COLOR FOR WHITIE	2	PCS
③	CONNECTOR 2	DP 20P/FEMALE, HOUSING FOR BLACK PLASTIC, TERMINAL FOR Cu AND GOLD PLATED, THE SHELL FOR METAL AND GOLD PLATING+PCBA (IC IO363)	1	PCS
②	CONNECTOR 1	USB TYPE C MALE, HOUSING FOR BLACK PLASTIC, TERMINAL FOR Cu AND GOLD PLATED, THE SHELL FOR METAL AND GOLD PLATING+10uF	1	PCS
①	TYPE C CABLE	(1/0.20BC*1P+AL)*4C+1/0.20BC*1P+1/0.20BC*4C+41/0.08BC*2C+AL, BLACK TPU JACKET, OD: 4.8±0.2mm	1	PCS

Pack Draw:



Approved		Reviewer		Drawing		Drawing No.		TYO***		MC-USBCDP-A			
Emil Olsen		Franck		Xu.gy		ITEM No.		TYPE C/M-DP 20P/F-***M (GOLD)					
						Customer Name				TYPE C TO DP 20P/F CABLE L=0.2M(GOLD)			
						Unit		mm					
						Graphic				Tolerance		X. ±1.00 X.X ±0.50	