

MPN: HDM19191V2.0A

## HDMI 2.0 Cable, 270° angled, 1m

HDMI (High Definition Multimedia Interface) is one of the most used and acknowledged connections when transferring video and audio digitally from a source to a video display device or other compatible devices. This HDMI 2.0 cable is a High Performance and High Speed cable. It supports transfers up to 18 Gbps. It supports resolutions up to 4K@60Hz with HDCP 2.2, CEC, ARC and 3D. This cable is angled 270° and the design of the plug makes possible only to stick out 16mm from the wall. This is perfect when you need to install it in a flat screen, DVD player or anything like this close to the wall.



- 4K2K (60Hz), 4K2K (30Hz), 1080p (3D) (3840\*2160p), including 3D video
- Gold-Plated Connectors
- Transfer rate : 18 Gbit/s
- HDCP 2.2
- Support ARC (Audio Return Channel)
- Support HDR (High Dynamic Range)
- Support CEC (Consumer Electronics Control)
- Integrated Ethernet channel which saves additional network or audio cables
- Angled plug 270°

## Specifications

Features		
3D		Yes
Audio Return Channel (ARC)		Yes
AWG wire size		30
Cable length		1 m
Cable material		Copper
Connector 1		HDMI Type A (Standard)
Connector 1 form factor		Straight
Connector 1 gender		Male
Connector 2		HDMI Type A (Standard)
Connector 2 form factor		Angled
Connector 2 gender		Male
Connector contacts plating		Gold
Data transfer rate		18 Gbit/s
HDCP		Yes
HDCP version		2.0
HDMI Ethernet channel		Yes
HDMI version		2.0
High Dynamic Range (HDR) supported		Yes
Maximum resolution		3840 x 2160 Pixels
Product colour		Black
Quantity per pack		1 pc(s)
RoHS compliance		Yes

<b>Other features</b>	<b>Quantity</b>	1
<b>Package dimensions</b>	<b>Depth (package,cm)</b>	21 cm
	<b>Gross Weight (Package, kg)</b>	0.07 kg
	<b>Height (package,cm)</b>	2.4 cm
	<b>Width (package,cm)</b>	27.1 cm
<b>Product dimensions</b>	<b>Net Weight (Product, kg)</b>	0.05 kg
<b>Vendor information</b>	<b>Brand Name</b>	MicroConnect
	<b>Warranty</b>	25 Year(s)
<b>Weight &amp; dimensions</b>	<b>Cable diameter</b>	6 mm

## Other products in this series

Cable length	
0.5	HDM191905V2.0A
1.0	HDM19191V2.0A
1.5	HDM191915V2.0A
2.0	HDM19192V2.0A
3.0	HDM19193V2.0A
5.0	HDM19195V2.0A