www.transcend-info.com





🕤 Transceno

Dashcams DrivePro[™] 10

Featuring a compact, minimalist design, Transcend's DrivePro 10 dashcam comes equipped with the STARVIS[™] high-sensitivity image sensor to capture high-resolution images with extremely fine tonal gradation even in low light; a 140° wide angle lens offering the best coverage of the road; up to 1080P Full HD recording at 60fps to capture every crucial detail; Wi-Fi connectivity for live monitoring on your smart gadgets; and emergency recording for optimum protection.



Vision in the dark

The DrivePro 10 features the STARVIS™ image sensor to capture sharp, high-resolution images in superb, rich color even in low light, making it perfect for filming during both day and night. It is equipped with a 140° wide-angle lens, providing a broad field of view.



Compact and discreet

The DrivePro 10 comes in a compact, discreet design that allows it to be flexibly mounted on your front or rear windshield. Being able to easily hide behind the rearview mirror out of sight, the DrivePro 10 offers the driver an unobstructed view of the road ahead or behind.



Get super smooth, detail-packed footage

Supporting 1080P Full HD recording at 60fps, the DrivePro 10 will give you footage as smooth as butter. Shooting at 60fps means you can zoom in on any shot and easily make out crucial details, such as license plates.

Note: STARVIS is a trademark of Sony Corporation.





Dashcams DrivePro[™] 10

Features

- STARVIS high-sensitivity image sensor for filming at night
- 140° wide angle lens for the best field of view
- \cdot Up to 1080P Full HD recording at 60fps
- Built-in battery ensures uninterrupted recording
- Emergency recording prevents overwriting of the current recorded file

Specification

Appearance			
Dimensions	58.3mm x 36mm x 22.8mm (2.3" x 1.42" x 0.9")		
Weight	40g (1.41 oz)		
Interface			
USB Type	micro USB to car lighter adapter		
Connection Interface	USB 2.0		
Hardware			
Viewing Angle for Lens	140° (diagonal)		
Aperture	F/2.0		



DrivePro Toolbox Software

In addition to playback, Transcend's DrivePro Toolbox features a sorting function to quickly locate video clips by file name, recording date, or group. The DrivePro Toolbox also provides a screenshot function allowing for the capture of a single frame.

Operating Environment

operating Linnoning	
Operating Temperature	-20°C (-4°F) ~ 60°C (140°F)
Storage Temperature	-25°C (-13°F) ~ 70°C (158°F)
Input Voltage	12V ~ 24V
Output Voltage	5V / 2A
Format	
Resolution	Full HD 1080P
Frame Rate	30/60 fps
Video Format	MP4 (H.264)
Warranty	
Certificate	CE/FCC/BSMI/KC
Warranty	Two-year Limited Warranty

Ordering Information

32GB

TS-DP10A-32G

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



Dashcams Comparison



DrivePro[™] 550







DrivePro[™] 230

DrivePro[™] 110

DrivePro[™] 10

x 40.5 mm x 34.5 mm x 32.5 mm Weight (Max.) 107 g (3.77 oz) 81 g (2.86 oz) 69g (2.43 oz) Interface micro USB micro USB micro USB micro USB micro USB to car lighter adapter to car lighter to ca					
South A0, Smith 7.02, Init X 05, Imith 7.02, Imit X 05, Imit X 05, Imith 7.02, Imit X 05, Imit					Appearance
Interface Interface ISP Provide Stress Provided Stress Provide	58.3mm x 36mm x 22.8mm				Dimensions (Max.)
USB Type micro USB to car lighter adapter to car lighter adapter Connection Interface USB 2.0 USB 2.0 USB 2.0 USB 2.0 USB 2.0 Network Interface Wi-Fi 802.11n Wi-Fi 802.11n - - Hardware Display 2.4° color TFT LCD 2.4° color TFT LCD 2.4° color TFT LCD 2.4° color TFT LCD - Viewing Angle for Lens 160° (diagonal) 130° (diagonal) 140° (diagonal) - Viewing Angle for Rear Lens 110° (diagonal) - - - - Viewing Angle for Rear Lens F/2.2 F/2.0 F/2.0 - - Infrared LEDs V - - - - - Dual Lens Camera V V V V - - - Built-In Battery V V V V - - - Coroninates V V V - -	40g (1.41 oz)	69g (2.43 oz) 40	81 g (2.86 oz)	107 g (3.77 oz)	Weight (Max.)
USB Type micro USB to car lighter adapter to car lighter adapter Connection Interface USB 2.0					Interface
Network Interface Wi-Fi 802.11n Wi-Fi 802.11n - Hardware -	micro USB car lighter adapter				USB Type
Hardware Hardware Display 2.4" color TFT LCD 2.4" color TFT LCD 2.4" color TFT LCD 2.4" color TFT LCD Viewing Angle for Lens 160° (diagonal) 130° (diagonal) 140° (diagonal) 1 Viewing Angle for Rear Lens 110° (diagonal) - - - Aperture (Rear) F/2.2 F/2.0 F/2.0 - Aperture (Rear) F/2.8 - - - Infrared LEDs V - - - GPS Coordinates V V - - Built-in Battery V V V V Snapshot V V V V Speaker V V V V Format V V - - Resolution (Rear) Full HD 1080P Full HD 1080P Full HD 1080P - Frame Rate 30 fps 30 fps 30/60 fps - Video Format . . - - <tr< td=""><td>USB 2.0</td><td>USB 2.0</td><td>USB 2.0</td><td>USB 2.0</td><td>Connection Interface</td></tr<>	USB 2.0	USB 2.0	USB 2.0	USB 2.0	Connection Interface
Display 2.4" color TFT LCD 2.4" color TFT LCD 2.4" color TFT LCD Viewing Angle for Lens 160° (diagonal) 130° (diagonal) 140° (diagonal) 1 Viewing Angle for Rear Lens 110° (diagonal) - - - Aperture (Rear) F/2.2 F/2.0 F/2.0 - Aperture (Rear) F/2.8 - - - Image Sensor Exmor ^M Exmor ^M STARVIS ^M - Infrared LEDs V - - - Dual Lens Camera V V - - - Built-in Battery V V V V -	Wi-Fi 802.11n	- Wi	Wi-Fi 802.11n	Wi-Fi 802.11n	Network Interface
Viewing Angle for Lens 160° (diagonal) 130° (diagonal) 140° (diagonal) 1 Viewing Angle for Rear Lens 110° (diagonal) - - - Aperture F/2.2 F/2.0 F/2.0 - Aperture (Rear) F/2.8 - - - Infrage Sensor Exmor [™] Exmor [™] STARVIS [™] - GPS Coordinates V - - - - Dual Lens Camera V V -					Hardware
Niewing Angle for Rear Lens 110° (diagonal) - Aperture F/2.2 F/2.0 F/2.0 Aperture (Rear) F/2.8 - - Image Sensor Exmor™ Exmor™ STARVIS™ Infrared LEDs V - - GPS Coordinates V V - Dual Lens Camera V V - Built-in Battery V V V GS Sensor V V V Snapshot V V V Microphone V V V Wi-Fi V V V Wi-Fi V V V Resolution (Rear) Full HD 1080P Full HD 1080P Full HD 1080P Frame Rate 30 fps 30 fps 30/60 fps Video Format .MP4 (H.264) .MOV (H.264) .MP4 (H.264) Lane Departure Warning System V V - Forward Collision Warning System V V	-	2.4" color TFT LCD	2.4" color TFT LCD	2.4" color TFT LCD	Display
ApertureF/2.2F/2.0F/2.0Aperture (Rear)F/2.8-Image SensorExmor ^{IM} Exmor ^{IM} STARVIS ^{IM} Infrared LEDsV-GPS CoordinatesVVDual Lens CameraV-Built-in BatteryVVG-SensorVVG-SensorVVSnapshotVVVVVSpeakerVVVVVFormatVVFormatSol fps30 fpsResolution (Rear)HD 720P-Frame Rate30 fps30 fpsSolof SystemVVFormatVVFormatVVFormatVVFormatVVFame Rate30 fps30 fpsSolution Warning SystemVVVV-Forward Collision Warning SystemVVVV-Head-up displayV-Headlight reminderVVVV-	140° (diagonal)	140° (diagonal) 140	130° (diagonal)	160° (diagonal)	Viewing Angle for Lens
Aperture (Rear) $F/2.8$ -Image Sensor $Exmor^M$ $Exmor^M$ $STARVIS^M$ Infrared LEDsV-GPS CoordinatesVVDual Lens CameraV-Built-in BatteryVVG-SensorVVSnapshotVVMicrophoneVVSpeakerVVW-FiVVFormatFull HD 1080PFull HD 1080PResolution (Rear)HD 720P-Frame Rate30 fps30/fpsSolor SynapshotVVViceo FormatVVResolution (Rear)HD 720P-FormatVV-FormatVV-FormatVV-FormatVV-Fame Rate30 fps30/fps30/fol fpsVideo FormatVV-Forward Collision Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVHeadlight reminderVV-	-	-	-	110° (diagonal)	Viewing Angle for Rear Lens
Exmor™Exmor™STARVIS™Infrared LEDsVGPS CoordinatesVV-Dual Lens CameraVBuilt-in BatteryVVVG-SensorVVVSnapshotVVVMicrophoneVVVSpeakerVVVSpeakerVVVFormatVVVResolution (Rear)HD 720PFrame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)FormatVV-FormatVV-Frame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)Forward Collision Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVVV-Headlight reminderVVV-	F/2.0	F/2.0	F/2.0	F/2.2	Aperture
Infrared LEDs V - Infrared LEDs V - GPS Coordinates V V Dual Lens Camera V - Built-in Battery V V GS Sensor V V GS Sensor V V Snapshot V V Microphone V V Speaker V V V V V Speaker V V Vi-Fi V V Format V V Resolution (Rear) Full HD 1080P Full HD 1080P Full HD 720P - - Frame Rate 30 fps 30/60 fps Video Format .MP4 (H.264) .MOV (H.264) .MP4 (H.264) Lane Departure Warning System V V - Forward Collision Warning System V V - Head-up display V - -	-	-	-	F/2.8	Aperture (Rear)
Kindex Gamera V V - Dual Lens Camera V - - Built-in Battery V V V Built-in Battery V V V G-Sensor V V V G-Sensor V V V Snapshot V V V Snapshot V V V Microphone V V V Speaker V V V Wi-Fi V V V Format - - - Resolution (Rear) Full HD 1080P Full HD 1080P Full HD 1080P Resolution (Rear) HD 720P - - Frame Rate 30 fps 30 fps 30/60 fps Video Format .MP4 (H.264) .MOV (H.264) .MP4 (H.264) Technology	STARVIS™	STARVIS™ S	Exmor™	Exmor™	Image Sensor
Dual Lens Camera V - Built-in Battery V V V Scensor Full HD 1080P Full HD 1080P Full HD 1080P Resolution (Rear) HD 720P - - Frame Rate 30 fps 30 fps 30/60 fps v/ideo Format .	-	-	-	V	nfrared LEDs
Built-in BatteryVVVBuilt-in BatteryVVVG-SensorVVVSnapshotVVVSnapshotVVVMicrophoneVVVSpeakerVVVWi-FiVVVFormatVV-Resolution (Rear)HD 720PFrame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)TechnologyVV-Head-up displayVV-Headlight reminderVV-	-	-	V	V	GPS Coordinates
Gold in FockeryVVG-SensorVVVSnapshotVVVMicrophoneVVVSpeakerVVVSpeakerVVVFormatVV-Resolution (Rear)Full HD 1080PFull HD 1080PFull HD 1080PFrame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)Lane Departure Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVV-Video FormindVV-	-	-	-	V	Dual Lens Camera
ShapshotVVSnapshotVVMicrophoneVVSpeakerVVWi-FiVVFormatVVResolution (Rear)Full HD 1080PFull HD 1080PFull Resolution (Rear)HD 720P-Frame Rate30 fps30 fps30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264)TechnologyV-Lane Departure Warning SystemVVVHead-up displayV-VV-VV-	V	V	V	V	Built-in Battery
MicrophoneVVMicrophoneVVSpeakerVVWi-FiVVFormatFull HD 1080PFull HD 1080PResolution (Rear)HD 720P-Frame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)FechnologyVV-Forward Collision Warning SystemVV-Head-up displayVV-Headlight reminderVVV	V	V	V	V	G-Sensor
Number of the second speakerVVVSpeakerVVVWi-FiVV-FormatFull HD 1080PFull HD 1080PFull HD 1080PResolution (Rear)HD 720PFrame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)TechnologyVV-Forward Collision Warning SystemVV-Head-up displayVV-Wead-up displayVVV	-	V	V	V	Snapshot
SpeakerVV-Wi-FiVV-FormatFull HD 1080PFull HD 1080PFull HD 1080PResolution (Rear)HD 720PFrame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)TechnologyVV-Forward Collision Warning SystemVV-Head-up displayVV-Wiedelight reminderVVV	V	V	V	V	Microphone
FormatFormatResolutionFull HD 1080PFull HD 1080PResolution (Rear)HD 720P-Frame Rate30 fps30 fps30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264)FechnologyV-Lane Departure Warning SystemVVForward Collision Warning SystemVVVead-up displayV-Headlight reminderVVV	-	V	V	V	Speaker
ResolutionFull HD 1080PFull HD 1080PFull HD 1080PResolution (Rear)HD 720PFrame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)TechnologyVV-Lane Departure Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVV-VVV-	V	-	V	V	Wi-Fi
Resolution (Rear)HD 720P-Frame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)TechnologyVV-Lane Departure Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVV-Verdified ForminderVVV					Format
Frame Rate30 fps30 fps30/60 fpsVideo Format.MP4 (H.264).MOV (H.264).MP4 (H.264)Fechnology.MP4 (H.264)Lane Departure Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayV·-Headlight reminderVVV	Full HD 1080P	Full HD 1080P Ful	Full HD 1080P	Full HD 1080P	Resolution
Video Format.MP4 (H.264).MOV (H.264).MP4 (H.264)FechnologyLane Departure Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVHeadlight reminderVVV	-	-	-	HD 720P	Resolution (Rear)
FechnologyLane Departure Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVHeadlight reminderVVV	30/60 fps	30/60 fps	30 fps	30 fps	Frame Rate
Lane Departure Warning SystemVV-Forward Collision Warning SystemVV-Head-up displayVHeadlight reminderVVV	.MP4 (H.264)	.MP4 (H.264) .M	.MOV (H.264)	.MP4 (H.264)	Video Format
Forward Collision Warning System V V - Head-up display V - - Headlight reminder V V V					Геchnology
Head-up displayV-Headlight reminderVVV	-	-	V	V	Lane Departure Warning System
Headlight reminder V V V	-	-	V	V	Forward Collision Warning System
	-	-	-	V	Head-up display
	-	V	V	V	Headlight reminder
Driver fatigue alert V V V	-	V	V	V	Driver fatigue alert
Emergency recording V V V	V	V	V	V	Emergency recording

Note: Exmor/STARVIS is a trademark of Sony Corporation.