

## MPN: USB3.1CCOM14

USB-C, 2 x USB3.0 A, RJ45, HDMI, VGA, Type C, Dock, hub

USB-C to 2 x USB 3.2 Gen 1 A /RJ45/ HDMI/VGA/Type C Data or PD charging Adapter Dock, hub

- Operation System Support :Windows XP/Vista/Win 7/8/8.1/10/Mac OS 10.5 or later
- Thunderbolt 3 Compatible
- Power delivery up to 100W
- HDMI resolution up to 4k30Hz
- VGA resolution up to 1920x1200 60Hz
- USB 3.0 and USB 3.1 Gen 1 are now identified as USB 3.2 Gen 1, offering data transfer speeds of up to 5 Gbps.



## Specifications

Network	Ethernet LAN	Yes
	Ethernet LAN (RJ-45) ports	1
	Ethernet LAN data rates	10, 100, 1000 Mbit/s
Operational conditions	Operating relative humidity (H-H)	10 - 85 %
	Operating temperature (T-T)	0 - 45 °C
	Storage relative humidity (H-H)	5 - 90 %
	Storage temperature (T-T)	-10 - 70 °C
Package dimensions (verified)	Depth Verified	15.8 cm
	Gross Weight Verified	0.092 kg
	Height Verified	1.7 cm
	Width Verified	27.8 cm
Performance	Card reader integrated	No
	Certification	FCC, CE
	Plug and Play	Yes
	Product colour	Grey
Ports & interfaces	Connectivity technology	Wired
	HDMI ports quantity	1
	Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
	Microphone in	No
	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
	USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
	USB Power Delivery	Yes
	USB Power Delivery up to	100 Watt
	VGA (D-Sub) ports quantity	1



Power	Output current	5 A
	Output voltage	20 V
	Power source type	USB
Product dimensions	Net Mainht (Due duet 1/2)	
	Net Weight (Product, kg)	0.05 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)



## Other images



