

# i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W

i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W



#### PRODUCT DESCRIPTION

Professional USB-C docking station with support for up to four external monitors. The docking station is equipped with hybrid image processing: it is built on DisplayLink and USB-C video transmission technologies, allowing it to process images on four display devices at the same time. The station is compatible with any laptop equipped with a USB-C port (with video transmission support) or Thunderbolt 3. 6x USB ports, reliable and quick connection to your company network thanks to an integrated LAN port and support for installation on the back of a monitor make the docking station an ideal partner for professionals. And of course, the station is capable of charging your laptop or tablet with up to 85 W.

- Connect up to 4 external monitors
- Power delivery: up to 85 W
- Provides 2 DisplayPorts and 2 HDMI ports
- 5x USB 3.0 and 1x USB-C ports will allow you to easily connect your USB devices and peripherals.
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- 2x jack for audio and microphone
- · Kensington lock protects against theft, particularly in shared offices or public spaces
- On/off switch for maximum energy savings
- The station features VESA support, allowing smart vertical installation on the back of a VESA compatible monitor
- Supports Windows 10, macOS\*, Android, and Linux

\* Note: macOS does not support Multi Stream Transport (MST) technology, meaning that when connected to a device running macOS, two of the four connected monitors will display the same image.

## **PRODUCT FEATURES**

- 1x USB-C port for connecting to a device
- Docking station technology: USB-C (MST) + DisplayLink 3900



- Power Delivery: 85W
- Video ports: 2x DisplayPort (DP++ support) 2x HDMI
- Resolution:
- DisplayLink ports (2x HDMI):
  - 1 monitor: up to 1440p/50Hz
  - 2 monitors: up to 1152p/60Hz
- USB-C DisplayPort Alt mode ports (2x DP):
- Host device with DisplayPort 1.2 support:
  - $\circ$  1 monitor → up to 4K/30Hz
  - 1 monitor → up to 1080p/120Hz
  - ∘ 2 monitors  $\rightarrow$  up to 2x 1080p/60Hz\*
- Host device with DisplayPort 1.4 support:
  - 1 monitor → up to 4K/60Hz
  - 1 monitor → up to 1440p/144Hz or 1080p/240Hz
  - ∘ 2 monitors  $\rightarrow$  up to 2x 1440p/60Hz\*
- Host device with DisplayPort 1.4 with DSC support:
  - 1 monitor → up to 5K/60Hz
  - $\circ$  1 monitor → up to 4K/144Hz or 1440p/240Hz or 1080p/360Hz
  - ∘ 2 monitors  $\rightarrow$  up to 2x 4K/60Hz\*
  - ∘ 2 monitors  $\rightarrow$  up to 2x 1440p/144Hz\*
- (Four monitor combination):
  - Up to 2x 2048×1152/60Hz and 2x 4K/60Hz
- 1x USB-C Gen. 1 port (data only)
- 4x USB 3.0 port
- 1x USB 3.0 port with Fast Charge support (BC 1.2)
- 1x Ethernet GLAN RJ-45 port (Realtek RTL8153)
- 1x 3.5mm Audio port
- 1x 3.5mm Mic port
- 1x port for power supply (DC 20 V/6.75 A)
- ON/OFF switch for the docking station
- LED indication
- Kensington lock support
- VESA mount support
- USB-C cable (100 cm)
- OS: Windows 10/11, macOS\*, iPadOS\*\*, Android\*\*, Chrome OS and Linux with latest updates
- Product dimensions: 197 x 85 x 34 mm
- Product weight: 296 g
- Package dimensions: 260 x 215 x 48 mm
- · Package weight: 1167 g

### **Hardware Requirements:**

Device with a free USB-C, USB4 or Thunderbolt<sup>™</sup> 3/4 port

## **Power Delivery Requirements:**

• Device with a free USB-C, USB4 or Thunderbolt™ 3/4 port with Power Delivery support

### **Video Output Requirements:**

Device with a free USB-C or USB4 port with DisplayPort Alternate Mode support or a Thunderbolt™ 3/4 port

## **Operating System:**

• Windows 10 / 11, macOS\*, iPadOS\*\*, Android\*\*, Chrome OS and Linux with latest updates



- \* macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.
- \*\* iPadOS, Android do not support multi-screen video transfer technology, nor the extended screen option. This means that when connected to an external monitor, only the mirrored screen will be displayed. (Not valid for androids with DEX and Easy Projection extension)

## **SPECIFICATION**

Part Number	Product Description & EAN
C31QUATTRODOCKPD	i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W EAN: 8595611703393
C31QUATTRODOCKPDUK	i-tec USB-C Quattro Display Docking Station with Power Delivery 85 W EAN: 8595611703409
Hardware	
Bus type	USB-C, Thunderbolt-3, Thunderbolt-4
Ports/Connectors	
System Requirements	
Operating system	Windows 10/11 macOS X Android Linux Chrome OS R51 or later
Other features	
Colour	black
Housing Material	ABS
Product Dimensions	197 x 85 x 34 mm
Product Weight	296 g
Package Weight	1167 g
Packaging Dimensions (LxWxH)	260 x 215 x 48 mm
Support	
Warranty period	2 years
Technical support	lifetime
Package contents	
Product	
USB-C cable (100 cm)	
Charging adapter (output: 20 V/6.75 A, 160 cm DC cable)	
Instruction manual	

For further information regarding setup or for answers to FAQ's, please visit our website <u>i-tec.pro</u>. Specifications are subject to change without notice.



Updated 16.2.2023